



# HPE OfficeConnect 1910 Switch Series



## Key features

- Customized operation using intuitive Web interface
- Layer 3 static routing with 32 routes for network segmentation and expansion
- Access control lists for granular security control
- Spanning Tree: STP, RSTP, and MSTP
- Limited Lifetime warranty

## Product overview

HPE OfficeConnect 1910 Switch Series consists of advanced smart-managed fixed-configuration Fast Ethernet switches designed for small businesses in an easy-to-administer solution. By utilizing the latest design in silicon technology, this series is one of the most power efficient in the market. The series is part of the OfficeConnect portfolio of Hewlett Packard Enterprise small business networking products.

The series consists of five Fast Ethernet models. The 8- and 24- port models include two dual-personality SFP ports to support fiber connectivity. The 48 port model has 2 dedicated SFP ports plus two 10/100/1000 Ethernet ports. The 8- and 24-port Fast Ethernet models are available with or without PoE.

All models support rack mounting or desktop operation. Customizable features include basic Layer 2 features like VLANs and link aggregation, as well as advanced features such as Layer 3 static routing, IPv6, ACLs, and Spanning Tree Protocols. HPE OfficeConnect 1910 Switch Series includes a Limited Lifetime Warranty.



**Management**

- Simple Web management  
Allows for easy management of the switch—even by nontechnical users—through an intuitive Web GUI; supports HTTP and HTTP Secure (HTTPS)
- Single IP management  
Enables management of up to four HPE OfficeConnect 1910 devices using a single Web interface; simplifies management of multiple devices
- Secure Web GUI  
Provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- SNMPv1, v2c, and v3  
Facilitates management of the switch, as the device can be discovered and monitored from an SNMP management station
- Complete session logging  
Provides detailed information for problem identification and resolution
- Dual flash images  
Provides independent primary and secondary operating system files for backup while upgrading
- Port mirroring  
Enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- Management security  
Restricts access to critical configuration commands; offers multiple privilege levels with password protection; ACLs provide telnet and SNMP access; local and remote syslog capabilities allow logging of all access
- Network Time Protocol (NTP)  
Synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- IEEE 802.1AB Link Layer Discovery Protocol (LLDP)  
Advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications
- Limited CLI  
Enables users to quickly deploy and troubleshoot devices in the network
- RMON  
Provides advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- Default DHCP client mode  
Allows the switch to be directly connected to a network, enabling plug-and-play operation; in the absence of a DHCP server on the network, the switch will fall back to a unique static address determined by the switch's MAC address



**Quality of service (QoS)**

- Broadcast control  
Allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic
- Rate limiting  
Sets per-port ingress-enforced maximums and per-port, per-queue minimums
- Traffic prioritization  
Provides time-sensitive packets (like VoIP and video) with priority over other traffic based on DSCP or IEEE 802.1p classification; packets are mapped to four hardware queues for more effective throughput

**Connectivity**

- IPv6
  - IPv6 host  
Enables switches to be managed and deployed at the IPv6 network's edge
  - IPv6 routing  
Supports IPv6 static routes
  - MLD snooping  
Forwards IPv6 multicast traffic to the appropriate interface, preventing traffic flooding
  - IPv6 ACL and QoS  
Supports ACL and QoS for IPv6 network traffic
- Auto-MDI/MDIX  
Adjusts automatically for straight-through or crossover cables on all 10/100/1000 ports
- IEEE 802.3x Flow Control  
Provides a flow-throttling mechanism propagated through the network to prevent packet loss at a congested node
- IEEE 802.3af Power over Ethernet (PoE) ready  
Provides up to 15.4 W per port to power standards-compliant IP phones, wireless LAN access points, Web cameras, and more (for PoE models)
- IEEE 802.3at Power over Ethernet (PoE+)  
Provides up to 30 W per port, which allows support of the latest PoE+-capable devices such as IP phones, wireless access points, and security cameras, as well as any IEEE 802.3af compliant end device; reduces the cost of additional electrical cabling and circuits that would otherwise be necessary in IP phone and WLAN deployments
- Packet storm protection  
Protects against broadcast, multicast, or unicast storms with user-defined thresholds
- Cable diagnostics  
Detects cable issues remotely using a browser-based tool



**Security**

- Advanced access control lists (ACLs)  
Enables network traffic filtering and enhances network control using MAC- and IP-based ACLs; time-based ACLs allow for greater flexibility with managing network access
- Secure Sockets Layer (SSL)  
Encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- IEEE 802.1X and RADIUS network logins  
Controls port-based access for authentication and accountability
- Automatic VLAN assignment  
Assigns users automatically to the appropriate VLAN based on their identity, location, and time of day
- STP BPDU port protection  
Blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- STP root guard  
Protects the root bridge from malicious attacks or configuration mistakes
- Automatic denial-of-service protection
- Monitors for malicious attacks and protects the network by blocking the attacks
- Management password  
Provides security so that only authorized access to the Web browser interface is allowed

**Performance**

- Half- or full-duplex auto-negotiating capability on every port  
Doubles the throughput of every port
- Selectable queue configurations  
Allows for increased performance by selecting the number of queues and associated memory buffering that best meet the requirements of the network applications
- IGMP snooping  
Improves network performance through multicast filtering, instead of flooding traffic to all ports
- Fiber uplink  
Provides greater distance connectivity using Gigabit Ethernet fiber uplinks



**Layer 2 switching**

- VLAN support and tagging  
Supports IEEE 802.1Q (4,094 VLAN IDs) and 256 VLANs simultaneously
- Spanning Tree Protocol (STP)  
Supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- BPDU filtering  
Drops BPDU packets when STP is enabled globally but disabled on a specific port
- Jumbo frame support  
Supports up to 10-kilobyte frame size to improve the performance of large data transfers

**Layer 3 services**

- Address Resolution Protocol (ARP)  
Determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- DHCP relay  
Simplifies management of DHCP addresses in networks with multiple subnets

**Layer 3 routing**

- Static IPv4 or IPv6 routing  
Provides basic routing (supporting up to 32 static routes and eight virtual VLAN interfaces); allows manual routing configuration

**Resiliency and high availability**

- Link aggregation  
Groups together multiple ports automatically using Link Aggregation Control Protocol (LACP), or manually, to form an ultra-high-bandwidth connection to the network backbone; helps prevent traffic bottlenecks; (8-port, 24-port and 48- port models support a maximum of 8 ports per trunk; the 8-port models supports 4 trunks; the 24-port model supports 8 trunks; the 48-port model support supports 16 trunks)



**Convergence**

- LLDP-MED (Media Endpoint Discovery)

Defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones

- PoE allocations

Supports multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user-specified) to allocate PoE power for more efficient energy savings

- Auto voice VLAN

Recognizes IP phones and automatically assigns voice traffic to dedicated VLAN for IP phones

**Additional information**

- Green initiative support

Provides support for RoHS and WEEE regulations

- Green IT and power

Improves energy efficiency through the use of the latest advances in silicon development; shuts off unused ports and utilizes variable-speed fans, reducing energy costs

**Warranty and support**

- Limited Lifetime Warranty

See [\*\*hpe.com/officeconnect/support\*\*](http://hpe.com/officeconnect/support) for warranty and support information included with your product purchase.



HPE OfficeConnect 1910 Switch Series



Specifications	HPE OfficeConnect 1910 8 PoE+ Switch (JG537A)	HPE OfficeConnect 1910 24 Switch (JG538A)
I/O ports and slots	<p>8 RJ-45 autosensing 10/100 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3at PoE+); Duplex: half or full</p> <p>2 dual-personality ports; each port can be used as a RJ 45 10/100/1000 Mbps port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) or as a SFP 100/1000 Mbps slot (IEEE 802.3u Type 100BASE-FX, IEEE 802.3z Type 1000BASE-X)</p> <p>1 RJ-45 console port to access limited CLI port</p> <p>Supports a maximum of 8 autosensing 10/100 ports plus 2 dual-personality ports either RJ-45 10/100/1000 port or SFP 100/1000 slot</p>	<p>24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</p> <p>2 dual-personality ports; each port can be used as a RJ 45 10/100/1000 Mbps port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) or as a SFP 100/1000 Mbps slot (IEEE 802.3u Type 100BASE-FX, IEEE 802.3z Type 1000BASE-X)</p> <p>1 RJ-45 console port to access limited CLI port</p> <p>Supports a maximum of 24 autosensing 10/100 ports plus 2 dual-personality ports either RJ-45 10/100/1000 port or SFP 100/1000 slot</p>
Physical characteristics		
Dimensions	12.99(w) x 9.06(d) x 1.73(h) in. (33 x 23 x 4.4 cm) (1U height)	17.32(w) x 6.81(d) x 1.73(h) in. (44 x 17.3 x 4.4 cm) (1U height)
Weight	4.63 lb (2.1 kg)	4.85 lb (2.2 kg)
Memory and processor	MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB	MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB
Mounting and enclosure	Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included)	Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included)
Performance		
100 Mb Latency	< 5 µs	< 5 µs
1000 Mb Latency	< 5 µs	< 5 µs
Throughput	up to 4.2 Mpps (64-byte packets)	up to 6.6 Mpps (64-byte packets)
Routing/Switching capacity	5.6 Gbps	8.8 Gbps
Routing table size	32 entries (IPv4), 32 entries (IPv6)	32 entries (IPv4), 32 entries (IPv6)
MAC address table size	8192 entries	8192 entries



Specifications	HPE OfficeConnect 1910 8 PoE+ Switch (JG537A)	HPE OfficeConnect 1910 24 Switch (JG538A)
<b>Environment</b>		
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Operating relative humidity	10% to 90%, noncondensing	10% to 90%, noncondensing
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Non-operating/Storage relative humidity	10% to 95%, noncondensing	10% to 95%, noncondensing
Acoustic	Pressure: 0 dB No Fan	Pressure: 0 dB No Fan
<b>Electrical characteristics</b>		
Frequency	50/60 Hz	50/60 Hz
AC voltage	100–240 VAC	100–240 VAC
Maximum power rating	90 W	12 W
PoE power	62 W	
	<b>Notes:</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS).	<b>Notes:</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A
<b>Management</b>	IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="https://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="https://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.



## HPE OfficeConnect 1910 Switch Series



### Specifications

#### HPE OfficeConnect 24 PoE+ Switch (JG539A)

#### HPE OfficeConnect 1910 48 Switch (JG540A)

### I/O ports and slots

24 RJ-45 autosensing 10/100 PoE+ ports  
(IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3at PoE+); Duplex: half or full

2 dual-personality ports; each port can be used as a RJ 45 10/100/1000 Mbps port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) or as a SFP 100/1000 Mbps slot (IEEE 802.3u Type 100BASE-FX, IEEE 802.3z Type 1000BASE-X)

1 RJ-45 console port to access limited CLI port

Supports a maximum of 24 autosensing 10/100 ports plus 2 dual-personality ports either RJ-45 10/100/1000 port or SFP 100/1000 slot

48 RJ-45 autosensing 10/100 ports  
(IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full

2 SFP 100/1000 Mbps slots (IEEE 802.3u Type 100BASE-FX, IEEE 802.3z Type 1000BASE-X)

2 RJ-45 autosensing 10/100/1000 ports  
(IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

1 RJ-45 console port to access limited CLI port

Supports a maximum of 48 autosensing 10/100 ports plus 2 autosensing 10/100/1000 ports plus 2 SFP 100/1000 slots

### Physical characteristics

#### Dimensions

17.32(w) x 9.37(d) x 1.73(h) in.  
(44 x 23.8 x 4.4 cm) (1U height)

17.32(w) x 6.81(d) x 1.73(h) in.  
(44 x 17.3 x 4.4 cm) (1U height)

#### Weight

7.28 lb (3.3 kg)

5.07 lb (2.3 kg)

### Memory and processor

MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB

MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 1.5 MB

### Mounting and enclosure

Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included)

Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included)

### Performance

#### 100 Mb Latency

< 5  $\mu$ s

< 5  $\mu$ s

#### 1000 Mb Latency

< 5  $\mu$ s

< 5  $\mu$ s

#### Throughput

up to 6.6 Mpps (64-byte packets)

up to 13.1 Mpps (64-byte packets)

#### Routing/Switching capacity

8.8 Gbps

17.6 Gbps

#### Routing table size

32 entries (IPv4), 32 entries (IPv6)

32 entries (IPv4), 32 entries (IPv6)

#### MAC address table size

8192 entries

8192 entries

### Environment

#### Operating temperature

32°F to 104°F (0°C to 40°C)

32°F to 104°F (0°C to 40°C)

#### Operating relative humidity

10% to 90%, noncondensing

10% to 90%, noncondensing

#### Non-operating/Storage temperature

-40°F to 158°F (-40°C to 70°C)

-40°F to 158°F (-40°C to 70°C)

#### Non-operating/Storage relative humidity

10% to 95%, noncondensing

10% to 95%, noncondensing

#### Acoustic

Pressure: 51.3 dB; ISO 7779

Pressure: 0 dB No Fan



## HPE OfficeConnect 1910 Switch Series

Specifications	HPE OfficeConnect 24 PoE+ Switch (JG539A)	HPE OfficeConnect 1910 48 Switch (JG540A)
<b>Electrical characteristics</b>		
Frequency	50/60 Hz	50/60 Hz
AC voltage	100–240 VAC	100–240 VAC
Maximum power rating	220 W	22 W
PoE power	180 W	
	<b>Notes:</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS).	<b>Notes:</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A
<b>Management</b>	IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.



Standards and Protocols

(applies to all products in series)

Device management		RFC 2819 RMON	
General protocols	IEEE 802.1D MAC Bridges	IEEE 802.1w Rapid Reconfiguration of Spanning Tree	IEEE 802.3i 10BASE-T
	IEEE 802.1p Priority	IEEE 802.3 Type 10BASE-T	IEEE 802.3x Flow Control
	IEEE 802.1Q VLANs	IEEE 802.3ab 1000BASE-T	IEEE 802.3z 1000BASE-X
	IEEE 802.1s (MSTP)	IEEE 802.3ad Link Aggregation Control Protocol (LACP)	
MIBs	RFC 1213 MIB II	RFC 2573 SNMP-Notification MIB	RFC 2668 802.3 MAU MIB
	RFC 1493 Bridge MIB	RFC 2573 SNMP-Target MIB	RFC 2674 802.1p and
	RFC 2021 RMONv2 MIB	RFC 2613 SMON MIB	IEEE 802.1Q Bridge MIB
	RFC 2233 Interface MIB	RFC 2618 RADIUS Client MIB	RFC 2737 Entity MIB (Version 2)
	RFC 2233 Interfaces MIB	RFC 2620 RADIUS Accounting MIB	RFC 3414 SNMP-User based-SM MIB
	RFC 2571 SNMP Framework MIB	RFC 2665 Ethernet-Like-MIB	RFC 3415 SNMP-View based-ACM MIB
	RFC 2572 SNMP-MPD MIB	RFC 2667 IP Tunnel MIB	RFC 3418 MIB for SNMPv3
Network management		IEEE 802.1D (STP)	RFC 1215 SNMP Generic traps
QoS/CoS		IEEE 802.1p (CoS)	
Security		IEEE 802.1X Port Based Network Access Control	



## HPE OfficeConnect Switch Series accessories

### Transceivers

HPE X110 100M SFP LC LX Transceiver (JD120B)  
HPE X120 1G SFP LC SX Transceiver (JD118B)  
HPE X120 1G SFP LC LX Transceiver (JD119B)  
HPE X120 1G SFP RJ45 T Transceiver (JD089B)

Learn more at  
[hpe.com/networking/smb](https://hpe.com/networking/smb)



Products within this series have achieved sufficient scores in each of the rated criteria to achieve the Miercom Certified Green distinction Award. See the Specifications section of this series for more information.



Make the right purchase decision. Click here to chat with our presales specialists.



Sign up for updates