

T Series IP Camera

ONL-T3620



Series	T Series 2MP, H.264+, 2.8 ~ 12 mm Varifocal Lens, Digital WDR, Bullet Type
---------------	---

Camera

Image Sensor	1 / 2.8 "CMOS
Image Size	1920 x 1080
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.1 lux @ F1.2, AGC ON; 0 lux with IR
Lens	2.8 ~ 12 mm @ F1.4, angle of view : 96° ~ 35°
Lens Mount	M12 and Ø14 optional
Day & Night	ICR
Wide Dynamic Range	Digital WDR
Digital NR	3D DNR
Angle Adjustment	Any angle

Image

Video Compression	H.264+ / MJPEG
H.264 Compression	Baseline Profile / Main Profile / High Profile
Resolution	1080P (1920 x 1080), 720P (1280 x 720), D1, CIF, 480 x 240
Main Stream	60Hz : 1080P (1 ~ 30 fps) / 720P (1 ~ 30 fps) 50Hz : 1080P (1 ~ 25 fps) / 720P (1 ~ 25 fps)
Bit Rate	256 Kbps ~ 5 Mbps
Encode Mode	VBR / CBR
Quality	Five levels under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, sharpen, NR, etc. adjustable through client software or web browser
ROI	3 ROI

Interfaces

Network	RJ45
----------------	------

Functions

Remote Monitoring	IE browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 3 users ; Support multi-stream real time transmission
Network Protocol	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol	ONVIF
Storage	Network remote storage
Smart Alarm	Motion alarm
PoE	Yes
IR Distance	20 ~ 30m
Water-proof	IP66

Others

Power Supply	DC12V / PoE
Power Consumption	< 2W
IR Consumption ON	< 5W
Operating Environment	- 20 °C ~ 50 °C, 10 % ~ 90 % relative humidity
Dimensions (mm)	Ø87 x 219
Weight (net)	605g
Installation	Wall mounting

2 MP Network IR Water-proof Varifocal Lens Bullet Camera



- * 1080P (1920 x 1080) full real time coding
- * Max.resolution : 1920 x 1080
- * ICR auto switch, true day / night
- * 20 ~ 30 m IR night view distance
- * 3D DNR, digital WDR
- * ROI coding
- * PoE power supply
- * Support smart phone, iPad, remote monitoring
- * Support P2P
- * IP66 ingress protection
- * Support three streams

