

**Mini IP Bullet Camera**  
**ONL-52IR**
**OINONE**  
 your cctv choice


Hardware	
<b>Sensor</b>	<b>1/3" Progressive Scan CMOS 1.3 MP</b>
<b>Effective Pixels</b>	1280(H)×960(V)
<b>Min.Illumination</b>	0.01Lux/F1.2(COLOR), 0.001Lux/F1.2(B/W), 0Lux(IR On)
<b>Day/Night</b>	Auto,dual IR-Cut filter, DWDR
<b>IR LED</b>	<b>12PCS Laser LED IR 60M</b>
<b>Max S/N Ratio</b>	39dB
<b>Electronic Shutter</b>	Rolling Shutter
<b>Lens</b>	<b>2.8-12mm Vari-Focal Lens</b>
<b>Network Interface</b>	10/100M BASE-TX,RJ-45 connector
<b>RS485</b>	Default as RS485 port for PTZ, 1ch Alarm input or 1ch alarm output optional
Audio video encoding	
<b>Video Compression</b>	H.264 Main Profile;
<b>Resolution</b>	HD 960P (1280*960) 1-25fps
<b>Sub Stream</b>	CIF(352*288)/QVGA(320*240)/QCIF(176*144) 1-30fps
<b>Video Bitrate</b>	32Kbps~4Mbps,Supports CBR/VBR
<b>Privacy Mask</b>	<b>4 configurable regions</b>
<b>Auto Image Control</b>	Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Band Filter (ABF)
<b>Functions</b>	Auto Black Level Calibration (ABLC)
<b>Image Controls</b>	Color saturation, hue, gamma, sharpness , lens correction, defective pixel canceling, and noise canceling
Data trans. & Storage	
<b>Data storage</b>	Video and Image
<b>Recording</b>	Recording set up to record by motion trigger,alarm trigger, manual, or schedule
<b>Alarm Output</b>	FTP,E-mail, Explorer, Software
<b>Network protocol</b>	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP
<b>ONVIF protocols</b>	Support 1.02 version
<b>Remote View</b>	IE 6.0 or later, max 10 users
General Parameters	
<b>Environmental Casing</b>	<b>Waterproof (IP66 Rated), Outdoor Use</b>
<b>Operating Temperature</b>	-20 °C ~ 50 °C (-4 °F ~ 122 °F) for DC 12V
<b>Operating Humidity</b>	0% -85% RH
<b>Power</b>	<b>PoE, DC12V 2.0A</b>
<b>Power Consumption</b>	9 W(MAX)
<b>Dimension</b>	268.7mmx108.4mmx89.9mm
<b>Weight</b>	780g
<b>Material</b>	Aluminum Alloy

**Dimensions**
