

Dynacom DN6025T SERIES 25CH 960P/16CH 1080P/9CH 3MP/4CH 5MP 2HDD



- P2P cloud service, including cloud connecting, cloud monitoring, cloud transmitting to access IPC and NVR at any time and any place
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard
- Support megapixel HD network video preview, storage and playback;
- Support search, playback and backup by event;
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream, and 4 channels playback;
- Support monitor PTZ on preview mode
- Offer CMS for free

Model Number	DN6025T	
Operating System	Embedded LINUX operating system	
Image Code Control	Image code quality adjustable, variable bitstream and constant bitstream optional	
Dual Stream	Each channel can set main stream and sub stream	
Video Standard	1080P(1920×1080)30fps/960P/(1280×960)/720P(1280×720)30fps	
Monitoring Image Quality	1080P(1920×1080) / 960P/(1280×960)/720P(1280×720)	
Image Motion Detection	Each screen can set multiple detection areas and set 6-level sensitivity	
Recording Playback Quality	1/4/8ch playback simultaneously.	
Region Cover	Every channel can set 4 cover regions (IPC Support)	
Recording Mode	Support manual auto, dynamic detection, alarm trigger record mode(Partly needs IPC Support)	
Backup Way	Support U disk, USB mobile HDD, USB DVD-RW. network storage and backup	
Operation Way	Mouse	
Local Login	Username and password	
Recording Storage	Local HDD, network	
External Ports	Video Input	①25×(1280*60)+sub[720*576]+4Ref.+8Play 25ch 1.3MP IP Camera
		②16×(1920*1080)+sub[960*576]+4Ref.+4Play 16ch 2.0MP IP Camera
		③9×(2048*1536)+sub[960*576]+4Ref.+4Play 9ch 3.0MP IP Camera
		④9x(2592*1944)+sub [960*576]+4Ref.+1Play 9ch 5.0MP IP Camera
	Audio Input	25/16ch network audio input
	Video Output	1ch VGA+1ch HDMI
	Audio Output	1ch RCA output
	Network Port	1 RJ45,10M/100M/1000M self-adaptive LAN port
	USB Port	2 USB 2.0 ports
Alarm Input	2ch(Optional)	
Alarm Output	1ch(Optional)	
Wireless Port	WIFI	
HDD	HDD Port	2 SATA HDD Ports
	MAX Capacity	Each port supports MAX 4TB HDD
Mobile Surveillance	Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone	
Power Supply	12V3A	
Power Consumption	≤20W (without HDD)	
Working Temperature	-10°C ~ +55°C	
Working Humidity	10%-90%	
Dimension	Equipment : 350mm×240mm×68mm, Packing : 409mm×365mm×129mm	
Weight(without HDD)	N.W. : 1.7Kg ; With packing : 2.9Kg	
Outside Carton	5 pcs/carton. 675mm×425mm×385mm ; Weight : 15.3 Kg	
Installation Way	Desktop Installation	