

# Dynacom WQ850AP

## Series Bullet Camera

5M pixel full real time optional  
2592x1944  
3.6mm (6MP Lens)  
Built-in IR-CUT.Low power consumption  
Micro SD 128GB support  
H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG  
Support Multiple-Stream  
Support ONVIF protocol



CAMERA	
<b>Model</b>	<b>WQ850AP</b>
Case	Metal, Bullet
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Max Resolution / FPS	2592x1944 / 20fps
Min. illumination	0.01Lux @ F1.2 (Color) (0 Lux IR LED On)
Day / Night	Day / Night with ICR Filter.
IR Leds	4pcs* $\phi$ , IR Range: 40M
Lens	3.6mm Fixed Lens
Lens Pixels	6MP
Video Output	Main stream:2592*1944@20fps, 1920*1080@30fps
	Sub stream:720*480@30fps
	Tri stream:352*288@30fps
PARAMETERS	
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	$\geq$ 52dB
NETWORK	
Network Port	One RJ45 Ethernet interface, 10M/100M self-adaption
Standard protocol	Onvif 2.4
Network Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
Mobile phone monitor	Support mobile phone monitor ( iPhone, iPad, Android, Android Pad)
IE Brower	IE8-11, Google Chrome, Firefox, Mac Safari
CONNECTOR	
Audio Input (Optional)	1CH audio MIC input/Line in
Audio Output (Optional)	1CH audio output
IO function port	Reset
Alarm in/output (Optional)	1* Alarm input port/1*Alarm output port
SD Card	Micro SD 128GB
GENERAL	
power	DC12V / PoE (802.3af) power input port, 5w power
Working Temperature	-20°C ~ +60°C RH95% Max
Housing	Metal, IP66
Product Dimensions	186(W) x 75(H) x 71(D)mm
Weight	500g