

Dynacom WQ8M13G 3G/4G Panoramic Camera



- 1.3 Megapixel
- 3G/4G GSM Camera
- H.264/MJPEG compression
- Support original view, panoramic view, 2/4/8 split-view
- Support two-way audio
- Wide Dynamic Range
- Digital Pan/Tilt/ Zoom
- Built in GSM/WCMA Modem
- Support Micro SD card local storage function
- Support POE, ONVIF
- Vandalproof

Model No.	WQ8M13G 3G/4G
CAMERA	
Sensor	1/3" Sony CMOS
Effective Pixels	1.3 Megapixels
Max. Resolution	1280*1024
Min. Illumination	0.01Lux@F2.0(Color)/0Lux@F2.0(B/W)
Day/Night	B/W/Color
IR Filter	Built-in auto switch IR Cut filter
Lens	Fisheye lens, f=1.16mm, F=2.0
Wide Dynamic Range	Digital WDR
Image Flip	Horizontal/Vertical
Image Adjustment	Brightness, saturation, sharpness, contrast, BLC,AWB
Panoramic Display	360° panoramic expansion-view,180° 2 split-view, 90° 4 split-view Longitude and latitude correcting view(wall mounted)
EPTZ	Digital Pan/Tilt/ Zoom
Intelligent Function	120 Regional Detection, Detection sensibility 1~6 adjustable
AUDIO/VIDEO COMPRESSION	
Video Compression	Dual Stream H.264 / MJPEG
Bit Rate	500Kbps~8Mbps
Max. Frame Rate	25fps
Microphone	Internal
Audio frequency	Support two-way audio
Audio Compression	G.711
NETWORK FUNCTION	
Alarm Trigger	Motion Detection
Alarm Action	Alarm Record/Image Snap, Alarm Video/Image Upload (FTP/Email)
Protocol	TCP/IP, HTTP, DHCP, DNS, RTP/RTSP, FTP, PPPOE, SMTP, NTP
Operating system	Windows 2000/XP/Vista/7
Compatibility	ONVIF 2.3
GENERAL	
Comm. Interface	1 RJ45 10M/100M Ethernet port
Power Interface	Φ5.5-2.1mm DC Socket
Local Storage	UP TO 128G Micro SD Card
Power Supply	DC12V±10% (2A) / POE
Power Consumption	<7W
Working condition	below 15°C~+50°C@humidity 10%~ 95%
Storage condition	below 40°C~+75°C@humidity 10%~ 95%
Protection Grade	IP66 for Metal type
Dimension	Product : 140(Diameter)*100(height)mm ; Package : 150×150×135mm
Gross Weight	Around 800g
Optional accessories	Mounting plate
Certificate	CE, RoHS, FCC



WDR



1.3 MP

