

EPN5210

2-Megapixel, 10x Optical Zoom,
Mini IR Network Speed Dome




ONVIF



Features

- Built-in 10x optical AF zoom
- Dual streams from H.264
- Easy and flexible installation
- Built-in network interface (10 / 100 Base-TX)
- True Day/Night function with removable IR cut filter
- Extended IR range of up to 80m / 260ft. with LEDs (Depending on scene IR reflectivity)
- Smart IR function eliminates overexposure problems
- Low luminance for better image quality at night
- Motion Detection
- Wide Dynamic Range (WDR)
- 3-Dimensional Noise Reduction (3DNR)
- From super slow [0.1°/sec] to very fast [240°/sec] pan / tilt speed
- 3D PTZ function
- Weather proof IP66-rated
- Maximum of 255 preset positions available
- Programmable auto pan / 4 tours / 4 patterns
- 1 alarm input and 1 alarm output
- Supports EverFocus' CMS and mobile applications
- ONVIF profile S compliant

Dimensions



Optional Accessories

Indoor Ceiling Pendant Mount

EPTZ-CLM

Indoor Ceiling Pendant Mount Bracket



Wall Mount

EPTZ-WMB

Enhanced Wall Mount Bracket



Keyboard

EKB200

USB controller keyboard



Specification

Model No.	EPN5210		
Pickup Device	Full HD Sony CMOS sensor	Horizontal Rotation Speed	0.1°/s ~ 200°/s (Manual) 240°/s (Preset)
Megapixel	2MP	Manual Pan / Tilt Speed	0.1°/s ~ 200°/s
Scanning System	NTSC / PAL	Position Accuracy	± 0.1°
Min. Illumination	Color: 0.05Lux@F1.6 (AGC-On) B/W: 0.005Lux@F1.6 (AGC-On) 0Lux With IR On	Horizontal Rotation Range	360°
S/N Ratio	≥50dB (AGC OFF)	Tilt Rotation Range	90°
Electronic Shutter	1/5 ~ 1/10,000sec.	Auto Pan Speed	45°/s
Optical Zoom	10x	Preset Positions	255 positions
Memory Card	Micro SD / SDHC card (up to class 10) (64G max.)	Running to Position Speed	300°/s
Aperture	F1.6 ~ F1.8	Tour	4 groups
Focus Length	5.1mm (wide) ~ 51mm (tele)	Pattern	4 patterns
Video compression	H.264	Interface	10 / 100 Base-T Ethernet, RJ-45 socket
Max. Video Resolution	1920 x 1080	Supported Protocols	TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS, DDNS, NTP, PPPoE, SMTP,FTP
Streaming Frame Rate	1 ~ 30fps (NTSC), 1~25fps (PAL)	Alarm	1 input / 1 output
Focus Control	Auto / Semi-Auto / Manual	Environmental Rating	IP66
Day/Night	True Day/Night with ICR	IR LEDs	6
Auto IRIS	DC-IRIS	IR Distance	Up to 80m / 260ft. (Depending on scene IR reflectivity)
Auto Gain Control	Yes	Power Source	24VDC / 24VAC~ / PoE
Backlight Compensation	Yes	Max Power Consumption	25W (24VDC & 24VAC~) / 30W (PoE IEEE 802.3at)
Wide Dynamic Range	Yes	Operating Temperature	-20°C ~ 55°C / -4°F ~ 131°F
3-Dimensional Noise Reduction	Yes	Humidity	0% ~ 90%
White Balance	Auto / White low lamp / 4000K / 5000K / Sunshine / Dark clouds / Flash light / Fluorescent lamp / High fluorescent lamp / Water bottom / Customized	Dimensions (H) x (Φ)	240 x 149mm / 9.45" x 5.87"
Motion Detection	Yes	Weight	2.7Kg / 5.90lb
Audio Compression	G.711	Certificates	CE, FCC, RoHS

Find Out More At:

EverFocus Taiwan HQ:
TEL: +886 2 2698 2334
www.everfocus.com.tw
marketing@everfocus.com.tw

EverFocus USA - California:
TEL: +1 626 844 8888
www.everfocus.com
sales@everfocus.com

International Branch Offices:
Germany, China, Japan

