

# DUNLOP DO-12E16D5T-IR

## HD1080P Turbo HD Bullet Jamera



### 9W W x 1 W x 1 W

- HD1080P Video Účjútú
- HDTVl Tejmknitrt
- True Day/Night
- OSD mené, 3D DNR, Smart IR
- 20m IR l dr`edrt
- IP66 jnqt l`rs`mc`qsc
- Jo`jr a`lk`msc(joaj rixdk jabln lid)
- 120 dB WCQ

DP-22E16D5T-IR	
<b>Jamera</b>	
Qdril Rdmdqé	1 / 3" Progressive Scan CMOS
Sinxal Sistemi	PAL / NTSC
@jste Onj rdk	1920(H)*1080(V)
Min. @xcómk`s l`	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter Gýč	1 / 25 s to 1 / 50,000 s
Lens	3.6mm (6mm optional) Angle of View: 80.9°(3.6mm), 54.3°(6mm)
Lens Moms`it	M12
Day & Night	ICR
@á: @x` q:	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
WCQ	120 dB
Sdmjgnmly` rxnm	Internal synchronization
Video J`qd Gýč	1080p@25fps / 1080p@30fps
HD Video Účjútú	1 Analog HD output
CVBS Účjútú	1Vp-p Composite Output(75Ω / BNC)
S / N Nq` mč	More than 52dB
<b>Mené</b>	
R`gmd	Indoor, Outdoor, Indoor1, LOW-LIGHT
Jamera ID	On / off (15 characters, position programmable)
AGC	Support
D / N Modt	Color / BW / EXT
Axd`y Cdmfdrh	ATW, AWC-SET, Indoor, Outdoor, Manual
L`rjdid l d	On / Off, maximum 8 zones
G`qjds @lfx` l`	On / Off, maximum 4 zones
BLC	Support
Sisqdü l Dmfdkd l d	On / off
Cik	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Fnmj rixnmk`q	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
<b>Genel</b>	
Ú`kú l`črc.c.md l h	-20 °C - 60 °C (-4 °F - 140 °F) Humidity 90% or less (non-condensing)
Féã J`xm`fc	12 VDC
Féã Séjds l h	Max. 4W
Jnqt l`Rs`mc`qsc	IP66
IR Ldr`edrt	20m
A`lk`msc`q	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Anxts`q	φ70×149.5 mm (φ2.76" ×5.89")
@lqpcj	360 g (0.79 lb)