

Compact one stop controller





PTZ/DVR System controller

SPC-2010

• 2 lines text LCD

- Up to 255 units of PTZ/zoom cameras, DVR, and receiver
- Compact design
- 3D joystick to control PTZ function
- Support multi-protocol

PTZ/DVR System controller

SPC-2010

Specifications



SPC-2010		
COMMUNICATION		
Interface		RS-485/422
Baud Rate		2,400 ~ 57,600bps
Control Equipment		PTZ/DVR/Receiver
Protocol	PTZ Camera	Samsung-T/E, Pelco-D/P, Panasonic, Vicon, AD, Honeywell , Bosch, Elmo, GE
	Zoom Camera	SCZ series
	DVR	SRD series(except SRD-480D)
	Receiver	Samsung-T(SRX-100B)
OPERATIONAL		
LCD display		16 x 2 character LCD, English
Joystick		3 Axis twist Zoom
Jog shuttle		DVR Play back control
ENVIRONMENTAL		
Operating Temperature		0 °C~ 40 °C
Operating Humidity		0~90%
ELECTRICAL		
Input Voltage		12V DC
Power Consumption		1.1W
MECHANICAL		
Dimension(WxHxD)		334.1 x 171.1 x 105.2 mm (13.15"x 6.74" x 4.14")
Weight		800g (1.76lb)

Dimensions

the mensions Unit : mm (inch)