

NEW

JVC

VN-H657BU Indoor camera

VN-H657WPBU Outdoor camera



**Direct Drive Super Fast, Slow and Accurate Pan/Tilt mechanism,
IP66 + IK10 housing*, performance at wide range temperature and super durable**

Features:

- 18x optical zoom, 360 deg. Endless PTZ
- SLL sensitivity 0.2 lux colour
- H.264 High profile /JPEG dual encode
- Fluent 30/30 fps dual stream [1080p+720p]
- True Day/Night for precise night monitoring
- 3DDNR, Privacy mask, Motion detection
- Alarm IN / OUT function
- Audio communication
- SD card recording
- PoE Plus / 24VAC power supply
- Built-in heater covering -40 deg/C operation [Outdoor model]
- Powerful ventilation design covering 60 deg/C [Outdoor model]
- IK10 Vandal resistant standard applied [Outdoor model]
- Optional bracket for versatile installation
- MTBF 66.000 H [Indoor mode] / 49.000 H [Outdoor model]

**2 million zooming!
4 million focusing!
5 million panning!**



SuperLoLux HD™

* IP66 Dust/Water proofed wall mount bracket included
IK10 Vandal resistant dome cover

JVC

Specifications:

		VN-H657BU	VN-H657WPBU
Camera, Lens and Pan/Tilt	Image device	Super LoLux 1 / 2.8 inch 2 Megapixel CMOS	
	Minimum. Illumination	Colour: 0.2 lx (AGC HIGH, x4, 50%) , 0.1 lx (AGC HIGH, x4, 25%), 0.35 lx (AGC HIGH, 25%), B&W: 0.08 lx (AGC HIGH, x4, 50%) , 0.04 lx (AGC HIGH, x4, 50%), 0.15 lx (AGC HIGH, 25%)	
	PTZ function	Direct Drive, 18x Optical, and 10x digital zoom, 100 preset positions Auto patrol / return / flip / trace / pan	
	Lens	F1.6 4.7 – 84.6 mm, Auto / Manual iris control	
	White balance	Manual / ATW-Wide / ATW-Narrow / ATW-Full / AWC	
	Sens-up	Yes (x32)	
	Noise reduction	3DNR	
	BLC	Yes (4 areas)	
	Day/Night	IR Cut filter On / Off	
	Scene file	8 patterns	
	Motion detect	Yes	
	Privacy mask	Yes (8 areas)	
	Panning	360 deg. endless type, Approx. 0.07 deg/sec to 400 deg/sec (at preset)	
	Tilting	-5 deg to 185 deg, Approx. 0.07 deg/sec to 400 deg/sec (at preset)	
Network	Picture resolution	1920x 1080, 1280x720, 640x360, 1280x960, 640x480, 320x240, 720x480, 352x240	
	Max frame rate	H.264 High Profile / Baseline : 30 fps, JPEG : 30 fps	
	Multi stream	1920x1080@30fps/H.264 HP, 720x480@30fps/H.264 HP 1920x1080@30fps/H.264 HP,720x480@30fps/MJPEG 1920x1080@30fps/H.264 HP,352x240@30fps/H.264 HP,352x240@30fps/MJPEG	
	Protocol	IPv4, HTTP, TCP, RTSP/RTCP/RTP, ICMP, UDP, IGMP, DNS, DHCP, ARP, NTP, FTP, SMTP, NTP JVC API, ONVIF v2.1	
	Internet explorer	IE 8/9 and IE10 on Windows 8	
General	Local recording	micro SDHC (Continuous recording / Alarm recording / Export by MPEG-4 format)	
	Audio communication	Yes (In/Out) mu-law	
	Alarm and trigger	Input (2), Output (2), Position, Sound/Motion/Tamper detect, Time, Day/Night, Fan stop	
	Dust and water protection	-	IP66
	Power	PoE Plus, 24VAC	
	Vandal protection	-	IK 10
	Temperature range	-10 to 50 deg/C	-40 (with built in heater) to 58 deg/C w/o SD card rec 60 deg/C with PoE Plus power supply
	Dimensions (WxHxD)	dia.160xH201mm	dia.260xH385xD350 mm
	Weight Approx	2.0 kg	5.6 kg
	Supported recorder	Network video recorder : VR-X1600U, VR-X3200U, SLLHD NVR Video management software : Aver, Avigilon, Axxon, Cathexis, Detec, Digifort, Exacq, EyelynX, Genetec, Geovision, GVD, Luxriot, Milestone, Mirasys, Netavis, Nice, Nuuu, Qnap, Seenergy, Seetec, Synology, Wavestore, Xtralis	
Optional bracket	3 types [Ceiling recessed, Wall, Pendant]	Pendant mount	
Regulation	CE, RoHS2, IEE 802.3(10Base-T), IEEE 802.3u(100Base-TX), IEEE802.3at(PoE Plus) FCC Part15 Class A, UL60950, EN60950, EN55022/2006+A1/2007<Class A>, GOST-R		

E. & O.E. Design and specifications are subject to change without notice.
All company names and product names maybe trademarks or registered trademarks of their respective owners. Any rights not expressly granted herein are reserved.
Copyright © 2013, JVCKenwood Corp. All Rights reserved.

