



700TVL High Resolution, High Sensitivity. 960H Analog Box Camera

The SCB-3003 belongs to the 960H premium WDR analog camera series that provides 700TV lines resolution with user-friendly and value added functions such as a motorised vari-focal lens, Day & Night, Privacy Masking ,Digital Noise Reduction and Video Analytics (That includes Fixed / Moved, Area, Fence, Tracking, Detection, Counting). The SCB-3003 provides clear images under a variety of challenging environment conditions, making it a perfect and practical solution for anyone looking for a cost effective high performance video surveillance camera.



Premium Resolution WDR Camera SCB-3003
















Accessories (Optional)



Accessories (Optional)				
SLA-3580DN	SLA-2812DN	SLA-550DV	SLA-612DN	
SLA-12240		A-880 S	STB-4150V	
SHB-4300H1 /4300H2/4300H3 SHB-4200/4200H				
and a	use with	Or H-500	STH-200	

	SCB-3003N	SCB-3003P		
VIDEO				
Imaging Device	1/3" Super HAD CCD II (Double scan)	1/3" Super HAD CCD II (Double scan)		
Total Pixels	1,028(H) x 508(V)	1,028(H) x 596(V)		
Effective Pixels	976(H) x 494(V)	976(H) x 582(V)		
Scanning System	2 : 1 Interlace			
Synchronization	Internal / Line lock / Extern			
Frequency	H : 15.734KHz / V : 59.94Hz	H: 15.625KHz/V: 50Hz		
Horizontal Resolution		11 . 13.023N127 V . 30112		
nonzoniai nesolulion	Color : 700TV lines (ER mode), B/W : 700TV lines			
Min. Illumination	Color: 0.1Lux@F1.2 (50IRE), 0.0002Lux (Sens-up, 512x) B/W: 0.01Lux@F1.2 (50IRE), 0.00002Lux (Sens-up, 512x)			
S / N Ratio	52dB (AGC off, Weight on)			
Video Output	CVBS : 1.0 Vp-p / 75Ω composite			
LENS				
Focus Control	Simple focus / Manual, Botton control (Manual, Simple focus, Day & Night)			
Lens Type	Manual / Auto iris (Video / DC)			
Mount Type	C/CS			
OPERATIONAL				
On Screen Display	English, Japanese, Spanish, French, Portuguese, Korean	English, French, German, Spanish, Italian, Chinese, Russian, Polish, Czech, Romanian, Serbian, Swedish, Danish, Turkish, Portuguese		
Camera Title	Off / On (Displayed 15 characters)			
Day & Night	Auto (ICR) / External / Color / B/W			
Backlight Compensation	Off / User BLC / HLC / WDR			
Wide Dynamic Range	128x (52dB)	160x (54dB)		
Contrast Enhancement	SSDR (Off / On)	100% (6 142)		
Digital Noise Reduction				
Digital Image Stabilization	SSNRIII (Off / On) Off / On			
Motion Detection				
	Built-in Off / On (12 programmable zapon with polygonal marking)			
Privacy Masking	Off / On (12 programmable zones with polygonal masking)			
Sens-up (Frame Integration)	2x ~ 512x			
Gain Control	Off / Low / High			
White Balance		ATW / Outdoor / Indoor / Manual / AWC (1,700°K ~ 11,000°K)		
Electronic Shutter Speed		1/60 ~ 1/120,000sec 1/50 ~ 1/120,000sec		
Digital Zoom	Off / On (1x ~ 16x)			
Reverse	Off / H-Rev / V-Rev / HV-Rev			
Profile	Basic / Day & Night / Backlight / ITS / Indoor / User			
Intelligent Video Analytics	Fixed / Moved, Fence, Tracking, Counting			
VPS	Off / On			
PIP	Off / On			
Alarm	1 Out			
Communication	Coaxial control (SPC-300 compatible), RS-485			
Protocol	Coax : Pelco-C (Coaxitron) RS-485 : Samsung-T/E, Pelco-D/P, Panasonic, Bosch, Honeywell, Vicon,GE, AD			
ENVIRONMENTAL				
Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F) / Less than 9	0% RH		
ELECTRICAL				
Input Voltage / Current	Dual (24V AC & 12V DC ±10%)			
Power Consumption	Max. 4W			
MECHANICAL	2010			
Color / Material	Black, Silver / Aluminum, Plastic			
Dimensions (WxHxD)	73.1 x 67.2 x 123.9mm (2.88" x 2.65" x 4.88")			
Weight				
vvcigill	285g (0.63 lb)			

The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive. eco

Design and specifications are subject to change without notice.







100 Challenger Rd. Suite 700 Ridgefield Park, NJ 07660 Toll Free: +1-877-213-1222 Direct: +1-201-325-6920

Fax: +1-201-373-0124

