

24-Ports PoE 10/100/1000Mbps Ethernet Switch

24-Ports PoE 10/100/1000Mbps + 4-Slots SFP



SFC 4000HP

- 802.3at PoE 30.8Watt (Max. 360W)
- Web Based Management, SNMP Management
- PoE Schedule : Exhaustion power reduction
- IGMP Snooping

Features

- 24-Ports(802.3at PoE) + 4-Slots SFP Management
- Auto Negotiation, Auto MDI-X
- Web Based Management, SNMP
- IGMP Snooping
- IEEE 802.1p Qos, Voip Qos
- IEEE 802.3at Power over Ethernet / PSE
- Port Mirroring
- Support IEEE 802.1 Q-in-Q LACP
- IEEE 802.1x user certification
- IEEE 802.1d & IEEE 802.1w Rapid Spanning Tree

Specifications

Technology	- Standard	IEEE 802.3 10Base-T IEEE 802.3z Gigabit SX/LX IEEE 802.1d Spanning tree protocol IEEE 802.1s Multiple spanning tree protocol IEEE 802.1Q VLAN Tagging IEEE 802.1x Port Authentication Network Control	IEEE 802.3u 100Base-TX/100Base-FX IEEE 802.3ab Gigabit 1000T IEEE 802.1w Rapid Spanning tree protocol IEEE 802.1p Class of Service IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet
Interface	- RJ45 Ports	10/100/1000Base-T RJ-45 24 Ports PoE, Combo Port(21~24), Auto-negotiation, Auto MDI-X	
	- Fiber Ports	4-SFP Slots, 1000Base-SX/LX SFP, 100Base-FX SFP, Speed auto detection	
	- LED Indicators	System : Power, Master, FAN Alert, PoE Power Alert Ports : 10/100/1000 Link/Act, PoE In-Use, SFP Link, Stack Port Link	
Performance	- Back Plane	Switch Fabric 48Gbps, Mac Address 8k, Jumbo Frame 10Kbytes	
	- PoE (Power over Ethernet)	Per Port 48VDC, 350mA, Max. 30.8 Watts Number of PD@7Watt / 24port Number of PD@15.4Watt / 23port Number of PD@30.8Watts / 11port	
Environmental	- Temperature	Operation: 0°C ~ 60°C, Store: -20°C ~ 80°C	
	- Humidity	5% ~ 95% (Non-condensing)	
Power Supply	- Input Voltage	100~240VAC, 50/60Hz	
Mechanical	- Dimensions	440mm (W) x 330mm (D) x 44.5mm (H), 4.5kg, 1U	