

(REGAL CODE. CC

GKB P3107 PnP IP Camera

Plug-and-Play IP Dome Camera

GKB P3107 is a network-ready camera for indoor use in residential and small-business surveillance installations. GKB P3107 delivers plug-and-play (PnP) networking when used with GKB zIP View[™] software, and this all-in-one design features dome housing, and 360° Dome Case Swivel.

Features:

• Plug & Play

GKB P3107 is a plug & play IP camera that makes network set-up easy. Once installed, set-up is as simple as entering ID and password using GKB zIP ViewTM software.

• MPEG4 Video Compression

GKB P3107 features MPEG4 video compression for superior video quality. Image quality is enhanced by avoiding the conversion of analog signals to digital before transmission.

• 360° Dome Case Swivel

GKB P3107 is equipped with specially designed 360° dome case swivel which make it simple for adjusting view angle without opening the dome housing.

3G Mobile Access

GKB P3107 enables 3G mobile surveillance by RTSP. With mobile version NVR, surveillance is done by simply entering ID and password, on most mobile phone of Windows Mobile, Symbian, and iPhone OS.





Video	Image Sensor	1/3" Sony CCD
	Number of Effective Pixels	NTSC: 510(H) * 492(V) PAL: 500(H) * 582(V)
	Video Compression	MPEG4
	Video Streams	2
	Resolution	176 * 120, 352 * 240, 720 * 480
	Frame Rate	Up to 30 FPS in All Resolutions
	Min. Illumination	0.3 Lux, 50 IRE, F1.4 / 0.01 Lux, 10 IRE, F1.4
	Gamma	0.45
	S/N Ratio	>48 dB
	Sync. Mode	Internal Sync
	Scanning System	2:1 Interlace
	Shutter Control	NTSC: 1/60-1/100,000 sec. PAL: 1/50-1/100,000 sec.
	BNC Video Output	1.0Vpp.75ohm
	Night Mode	Auto
	Auto Electronics Shutter	ON
	Auto Gain Control	ON
	Back Light Compensation	ON
	White Balance	ATW
Power	Power Supply	12V DC
	Power Consumption	3.6 W
Lens	3.6mm Board Lens (standard) 4.0/6.0/8.0 mm Board Lens (Optional)	
Dimension	82.6(H) * 117.5(Ø) mm	
Weight	0.5kg	
Operating Temperature	-10°C ~ 60°C	
Network	Protocol	HTTP, TCP, UDP, ICMP, RTSP, IGMP, RTCP, SMTP, FTP, UPnP DNS, DHCP, PPPoE
	Ethernet	10/100Mps Fast Ethernet RJ-45 Port
Software	Operating System	Windows XP and above
	Software Package	zIP View™ (36 CH. Management Software)

Dimensions





