

## D201-S XPT Q6055

## Real-time monitoring in hazardous areas

D201-S XPT Q6055 Explosion-Protected PTZ Network Camera is an easy-to-install and easy-to-integrate dome-style camera. It delivers the sweeping overviews and superb zoomed-in detail you expect from a top-of-the-line PTZ camera from Axis, but is also adapted for explosion-prone applications with Class I, Division 1 and Zone 1 certification. With low weight, PoE support for plug and play installation, and included AXIS T8154 60 W SFP Midspan for long-distance fiber-optic connection, D201-S XPT Q6055 offers significant savings. The camera is suitable for onshore, offshore, marine, and heavy industrial environments where you don't need to see above the horizon.

- > Certified for use in hazardous locations
- > Cost-efficient installation with PoE
- > Low weight and profile for simple installation
- > No need for power supply
- > Full HDTV 1080p with 32x optical zoom







## www.cxis.com T10123171/EN/M3.2/1807

## D201-S XPT Q6055

Camera Image sensor	1/2.8" progressive scan RGB CMOS		Pre- and post-alarm video or image buffering for recording or upload	
Lens	4.44–142.6 mm, F1.6–4.41 Horizontal field of view: 62.8°–2.23°		Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, day/night mode	
	Vertical field of view: 36.8°-1.3° Autofocus, auto-iris	Data streaming	Event data	
Day and night	Automatically removable infrared-cut filter	Built-in installation aids	Pixel counter	
Minimum illumination	Color: 0.3 lux at 30 IRE F1.6 B/W: 0.03 lux at 30 IRE F1.6	General		
mummation	Color: 0.5 lux at 50 IRE F1.6 B/W: 0.04 lux at 50 IRE F1.6	Casing	IP66-rated, electropolished SAE 316L stainless steel casing for maximum corrosion protection Prepared for American Petroleum Institute (API) DROP compliance, with additional safety wire for US offshore installations <sup>b</sup> US Patent 9917428	
Shutter time Pan/Tilt/Zoom	1/33000 s to 1/3 s with 50 Hz 1/33000 s to 1/4 s with 60 Hz Pan: 360° endless, 0.05°-450°/s			
1 any my 200m	Tilt: 220°, 0.05°–450°/s 32x optical zoom and 12x digital zoom, total 384x zoom, E-flip, 256 preset positions, Tour recording, Guard tour, Control queue, On-screen directional indicator, Set new pan 0°, Adjustable zoom	Memory	512 MB RAM, 128 MB Flash	
		Power	AXIS T8154 60 W SFP Midspan: 100–240 V AC, max 74 W Camera consumption: typical 16 W, max 60 W	
Video	speed	Connectors	8-position terminal block for PoE + ground, two M20 conduit entries	
Video	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles	Storage	Support for SD/SDHC/SDXC card	
compression Resolution	Motion JPEG  HDTV 1080p 1920x1080 to 320x180  HDTV 720p 1280x720 to 320x180		Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com	
Frame rate	Up to 60/50 fps (60/50 Hz) in HDTV 720p	Operating conditions	Safe area operating temperature: -50 °C to 50 °C (-58 °F to 122 °F)	
Video streaming	Up to 30/25 fps (60/50 Hz) in HDTV 1080p  Multiple, individually configurable streams in H.264 and Motion		Arctic Temperature Control: Start-up at -40 °C (-40 °F) Maximum temperature (intermittent): 60 °C (140 °F)	
	JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264		Hazardous location operating temperature: -20 °C to 55 °C (-4 °F to 131 °F) Humidity 10–100% RH (condensing)	
Image settings	Manual shutter time, compression, color, brightness, sharpness, white balance, exposure control, exposure zones, fine tuning of behavior in low light, rotation: 0°, 180°, text and image overlay, 32 individual 3D privacy masks, image freeze on PTZ, automatic defog, backlight compensation, Wide Dynamic Range (WDR): up to 120 dB depending on scene, highlight compensation	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	
		Certifications	Hazardous environment FM listed Class I, Division 1, Groups B, C and D, T6 Class I, Zone 1, IIB + H2 T6, -20 °C ≤ Ta ≤ +55 °C Certificate number: FM17US0156 Explosion	
Network Security	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption,		FM Class 3600:2011, FM Class 3615:2006, FM Class 3810:2005	
Security	IEEE 802.1X <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management	Approvals	EMC EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1 EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN32 Class A, KN35 Midspan EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB, KCC, UL-AR	
Supported protocols	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>*</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCIP, LLDP			
System integra	rtion	Dimensions	220 x 400 mm (8.60 x 15.82 in)	
Application Programming	Open API for software integration, including VAPIX®	Weight	28 kg (61 lb)	
Interface	and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profile S and ONVIF® Profile G, specification at onviforg	Included accessories	AXIS T8154 60 W SFP Midspan, two Allen keys, AXIS Surveillance Card 64 GB, Installation guide, Windows® decoder 1-user license	
Analytics	Included AXIS Video Motion Detection, autotracking, Active Gatekeeper,	Optional accessories	Wall Mount D201-S XPT, Pole Mount D201-S XPT	
	highlight compensation Basic Analytics (not to be compared with third-party analytics): Object removed, Enter/Exit detector, Fence detector, Object	Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on www.axis.com/vms	
	counter Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
Event triggers	Detectors: live stream accessed, video motion detection, shock	Warranty	Axis 3-year warranty, see www.axis.com/warranty	
	detection Hardware: fan, network, temperature, casing open Input signal: manual trigger, virtual inputs PTZ: autotracking, error, moving, preset reached, ready Storage: disruption, recording System: system ready	<ul> <li>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</li> <li>b. The camera has been developed in cooperation with Spectrum Camera Solutions, LLC</li> <li>Environmental responsibility:</li> </ul>		
Event actions	Time: recurrence, use schedule  Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email	www.axis.com/environmental-responsibility		

