

# AXIS M3114-VE

Home | Security | IP Domes | Megapixel Fixed

AXIS M3114-VE

1/4" Network Minidome, Fixed, Colour, H.264,

1280x800, Vandal Resistant, IP66, PoE

**Art-Nr. 200213**



## Main Features

1/4" CMOS progressive scan Network dome camera  
Resolution of 1280x800 to 160x90 px.  
Sensitivity of 1.0Lux at F2.0  
Lens: Fixed focal length F2.0/2.9mm  
Multiple H.264 and MJPEG streams  
Frame rate H.264&MJPEG: 25 Fps. in all resolutions

Digital PTZ functionality  
Video motion detection / Privacy zones  
Power-over-Ethernet (PoE, IEEE 802.3af)  
Vandalism resistant / Tampering alarm  
Protection rating: IP66  
Flat, discreet design / Easy installation

## Specifications

Series	Axis M31
System	colour
Sensor size	1/4"
Imager	CMOS
Sensitivity (at 50% video signal)	1,0 Lux, at F2.0
Digital Noise Reduction (DNR)	no
Low speed shutter	yes
Backlight compensation	BLC
Wide Dynamic Range (WDR)	no
IR cut filter	standard
Resolution max.	1280x800
Image transmission rate max.	25 B./Sek.
Activity detection	yes

# AXIS M3114-VE

(Continuation Specifications)

<b>Analysis functions</b>	no
<b>Video outputs</b>	no
<b>Audio support</b>	no
<b>Alarm inputs</b>	no
<b>Alarm outputs</b>	no
<b>Internal storage</b>	yes
<b>Compression standard</b>	H.264, MJPEG
<b>Ethernet interface</b>	10Base-T, 100Base-TX
<b>Network protocols</b>	IPv4, IPv6, HTTP, HTTPS, FTP, SMTP, DHCP, and more
<b>Lens type</b>	fixed focal length
<b>Lens mount</b>	integrated lens
<b>Focal length</b>	2,9 mm
<b>Horizontal angle of view</b>	80°
<b>Digital zoom</b>	no
<b>Iris control</b>	no
<b>Illumination</b>	no
<b>Serial interfaces</b>	no
<b>Remote configuration</b>	via web browser (Internet Explorer), remote software
<b>Password protection</b>	yes
<b>e-PTZ support</b>	yes
<b>Rotation range</b>	+/-180°
<b>Power over Ethernet</b>	yes, IEEE 802.3af
<b>Heater</b>	no
<b>Mounting</b>	flush mount
<b>Temperature range (operation)</b>	-20°C ~+50°C
<b>Vandalism resistant</b>	yes
<b>Housing</b>	outdoor, minidome
<b>Housing material</b>	aluminium, plastic
<b>Colour (housing)</b>	white
<b>Colour (bubble)</b>	clear
<b>Protection rating</b>	IP66, IP67
<b>Management Software Support</b>	Aimetis - Symphony, Axis - CamStation, Zelaris, Netavis
<b>ONVIF</b>	yes
<b>Certificates</b>	CE, IK08
<b>Supplier No.</b>	0413-001

## Optional accessories

<b>97649</b>	<b>AXIS T8412 INSTALL/DISPLAY</b>	Installation Display, Handheld Device, for Camera Setup, for Axis Cameras
--------------	-----------------------------------	---

## AXIS M3114-VE

97183	AXIS T90A37 W-LED 30-60 DEG	LED White Light Illuminator, 30-60° 50W, with Power Supply 100-240VAC
97617	AXIS T90A26 W-LED 50-100 DEG	LED White Light Illuminator, 50-100°, 25W, with Power Supply 100-240VAC
91498	AXIS POE MIDSPAN 1-PORT	1-Port Power-over-Ethernet Midspan
97757	AXIS P8221	Network I/O Audio Module, Preamplifier, 8 Inputs/ Outputs, Power Supply Unit
98572	AXIS M311X LENS TOOL 4PCS	Adjustment Tool for Viewing Direction, Focus, for Axis M311X, 4 Units

