

AXIS P1367-E Network Camera

Outdoor-ready 5 MP video in all light conditions

The 5 MP resolution at full frame rate ensures great video quality with a high level of details. The innovative outdoor-ready camera P1367-E is built for all weather conditions, with a quick and easy installation in mind. Built-in camera rails enable easier changing of lenses and with a simple roll of the sensor, the format shifts to Axis Corridor Format. In complex lighting or even in the dark, Forensic WDR together with Lightfinder will discover all details. Axis Zipstream technology optimizes the video stream saving bandwidth and storage while maintaining high video quality.

- > 5 MP resolution at 25/30 fps
- > Temperature range: -40 °C to 55 °C (-40 °F to 131 °F)
- > IK10-, IP66- and NEMA 4X-ratings
- > Lightfinder and Forensic WDR
- > Zipstream



AXIS P1367-E Network Camera

Camera		External output activation Video recording to edge storage, Play audio clip Pre- and post-alarm video buffering PTZ preset, Guard tour, Overlay text Day/Night switching, Status LED activation Send SNMP trap	
Image sensor	1/2.9" progressive scan RGB CMOS		
Lens	IR corrected, CS-mount lens, P-Iris Varifocal 2.8–8.5 mm, F1.2 With IK10 protection in the front window: Horizontal field of view: 72°–36° Vertical field of view: 40°–20° Without IK10 protection in the front window: Horizontal field of view: 83°–36° Vertical field of view: 45°–20°		
Day and night	Automatically removable infrared-cut filter	Data streaming	Event data
Minimum illumination	Color: 0.15 lux B/W: 0.03 lux, at 50 IRE F1.2	Built-in installation aids	Focus assistant, pixel counter, remote back focus
Shutter time	1/55500 s to 2 s	General	
Video		Casing	IP66-, IP67- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure Color: White NCS S 1002-B
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Sustainability	PVC free
Resolution	3072x1728 (5 MP) to 160x90	Memory	1 GB RAM, 512 MB Flash
Frame rate	25/30 fps (50/60 Hz) in all resolutions	Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 9.2 W, typical 5.3 W
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth	Connectors	RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm terminal block for two configurable inputs/outputs (12 V DC output, max. load 50mA) RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)
Multi-view streaming	Up to 8 individually cropped out view areas	Storage	Support for microSD/microSDHC/microSDXC card Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Image settings	Saturation, contrast, brightness, sharpness, forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, text and image overlay, privacy masks	Operating conditions	–40 °C to 55 °C (–40 °F to 131 °F) Maximum temperature (intermittent): 60 °C (140 °F) Humidity 10–100% RH (condensing)
Pan/Tilt/Zoom	Digital PTZ Uploadable PTZ driver (Pelco D pre-installed)	Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F)
Audio		Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1 Environment EN 50121-4/IEC 62236, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 62262 IK10 IEC/EN 60529 IP67
Audio streaming	Two-way, full duplex	Dimensions	382 x 155 x 120 mm (15 x 6.1 x 4.7 in)
Audio compression	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 8/16/32/48 kHz Configurable bit rate	Weight	2.2 kg (4.9 lb)
Audio input/output	External microphone input or line input, line output	Included accessories	Installation Guide, Windows decoder 1-user license, wall mount bracket, sunshield, connector kit IK10 tool
Network		Optional accessories	Axis mounts, Axis lenses, Axis midspans For more accessories, see www.axis.com
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log	Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/vms
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP [™] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
System integration		Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform, specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at www.onvif.org	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).</i>	
Analytics	AXIS Video Motion Detection, active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap	Environmental responsibility: www.axis.com/environmental-responsibility	
Event triggers	Analytics, open casing, edge storage events, external input, audio level, time scheduled		
Event actions	File upload: FTP, SFTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP		