

## AXIS P9106-V White

### Full coverage with ligature resistance

The 3 MP AXIS P9106-V Network Camera is specially designed for out-of-the-box optimized corner-to-corner coverage, at up to 130° horizontally and 95° vertically, without blind spots. It is enclosed in a vandal-resistant (IK10) and dust- and waterproof (IP66) casing. The abrasion- and chemical-resistant front window is easy to clean or replace, for efficient maintenance. AXIS P9106-V White is designed to be ligature-resistant, reducing the risk of vulnerable people using the camera for self-harm, e.g. in mental healthcare or custody cells. It is ideal for covering waiting rooms and interview rooms, especially when paired with portcast devices for two-way audio.

- > **Corner-mounted camera with ligature-resistant (anti-ligature) design**
- > **Out-of-the-box optimized field of view in 3 MP resolution - no blind spots**
- > **Vandal- and waterproof casing reduces impact of vandalism**
- > **Support for portcast devices, e.g. AXIS T61 Series**



# AXIS P9106-V White

Camera		
Image sensor	1/3" progressive scan RGB CMOS	
Lens	M12 mount, fixed focus, fixed iris 1.8 mm, F2.4 Horizontal field of view: 130° Vertical field of view: 95°	
Minimum illumination	Color: 0.35 lux at 50 IRE F2.4	
Shutter time	1/32500 s to 1/5 s	
Camera angle adjustment	Tilt ±5°	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	
Resolution	2016x1512 to 320x240 (4:3) 1920x1080 to 640x360 (16:9)	
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	
Multi-view streaming	2 individually cropped-out view areas	
Image settings	Saturation, contrast, brightness, sharpness, WDR, white balance, exposure mode, compression, privacy masks, orientation: auto, 0°, 90°, 180°, 270°, mirroring of images, text and image overlays	
Pan/Tilt/Zoom	Digital PTZ of view areas, preset positions, guard tours	
Network		
Security	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection	
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profile S and ONVIF <sup>®</sup> Profile G, specification at <a href="http://onvif.org">onvif.org</a>	
Analytics	Included AXIS Video Motion Detection, Active tampering alarm Supported AXIS Digital Autotracking, AXIS Motion Guard, Axis Fence Guard, Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>	
Event triggers	Analytics, edge storage events, virtual inputs through API	
Event actions	Video recording: to SD card or network share Upload of images or video clips: via FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text	
Data streaming	Event data	
Built-in installation aids	Pixel counter	
General		
Casing	IP66, IK10-rated Polycarbonate hard-coated dome Zinc and aluminum casing Color: white NCS S 1002-B	
		For repainting instructions and impact on warranty, contact your Axis partner.
Mounting	Corner mounting on 3 or 2 surfaces (wall + wall or wall + ceiling)	
Sustainability	PVC-free	
Memory	512 MB RAM, 256 MB Flash	
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 1 Typical 2.8 W, max 3.2 W Compatible with 2-wire converters Compatible with Axis PoE-over-Coax devices	
Connectors	RJ45 10BASE-T/100BASE-TX PoE	
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations, see <a href="http://axis.com">axis.com</a>	
Operating conditions	-15 °C to 50 °C (5 °F to 122 °F) Humidity 15–85% RH (non-condensing) Maximum operating temperature (intermittent): 55 °C (131 °F) Minimum startup temperature: 0 °C (32 °F)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	
Approvals	EMC EN 55032 Class A, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class B, KC KN35 Safety IEC/EN/UL 60950-1 Environment IEC/EN 60529 IP66, IEC/EN 62262 Class IK10, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 IEC 60721-3-5 5M3 (vibration, shock) Network NIST SP500-267	
Dimensions	Height: 92 mm (3.62 in) Width: 146 mm (5.74 in) Depth: 122 mm (4.80 in) Height when corner-mounted: 82 mm (3.23 in) Depth when corner-mounted: 104 mm (4.01 in)	
Weight	655 g (1.44 lb)	
Included accessories	Connector guard Installation guide Drill template Windows decoder 1–user license Extra screw gaskets Extra cable gaskets	
Optional accessories	AXIS P91 Skin Cover A Brushed Steel AXIS T6101 Audio and I/O Interface AXIS T6112 Audio and I/O Interface AXIS T864 PoE+ over Coax Series 2N <sup>®</sup> 2WIRE AXIS T8415 Wireless Installation Tool AXIS Surveillance Cards For more accessories, see <a href="http://axis.com">axis.com</a>	
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>	
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Polish, Portuguese, Traditional Chinese	
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://axis.com/warranty">axis.com/warranty</a>	

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).

Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)