

## AXIS Q1645

High-speed video with 1/2" sensor and i-CS lens

With AXIS Q1645 Network Camera it's easier than ever to capture details even in challenging lighting or low light. The 1/2" sensor and i-CS lens ensure sharp images in high resolution at full frame rate, and with Forensic WDR and Lightfinder, AXIS Q1645 provides superior light sensitivity and excellent image usability. AXIS Q1645 enables proactive surveillance with preinstalled AXIS Motion Guard and AXIS Fence Guard, and orientation aid with compass rose and street names for quick orientation with multiple monitors. Zipstream optimizes the video stream to maintain high video quality while saving bandwidth and storage.

- > **HDTV 1080p/2 MP resolution at up to 100/120 fps**
- > **1/2" sensor**
- > **Forensic WDR and Lightfinder**
- > **Electronic image stabilization (EIS)**
- > **AXIS Motion Guard and AXIS Fence Guard**



# AXIS Q1645

<b>Camera</b>	
<b>Image sensor</b>	1/2" progressive scan RGB CMOS
<b>Lens</b>	Varifocal, IR corrected, CS-mount 3.9–10.0 mm, F1.5 <b>2 MP (16:9):</b> Horizontal field of view: 109°–42° Vertical field of view: 58°–23° i-CS lens
<b>Day and night</b>	Automatically removable infrared-cut filter
<b>Minimum illumination</b>	<b>1080p 25/30 fps with WDR and Lightfinder:</b> Color: 0.05 lux, at 50 IRE F1.5, B/W: 0.01 lux, at 50 IRE F1.5 <b>1080p 50/60 fps with WDR and Lightfinder:</b> Color: 0.1 lux, at 50 IRE F1.5, B/W: 0.02 lux, at 50 IRE F1.5 <b>1080p 100/120 fps:</b> Color: 0.2 lux, at 50 IRE F1.5, B/W: 0.04 lux, at 50 IRE F1.5 <b>1080p 25/30 fps with WDR and Lightfinder:</b> Color: 0.02 lux, at 50 IRE F0.9, B/W: 0.004 lux, at 50 IRE F0.9
<b>Shutter time</b>	1/100000 to 2 s
<b>Pan/Tilt/Zoom</b>	Digital PTZ, uploadable PTZ driver (Pelco D pre-installed)
<b>Video</b>	
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profile Motion JPEG
<b>Resolution</b>	1920x1080 to 320x180
<b>Frame rate</b>	<b>HDTV 1080p (1920x1080) with WDR:</b> Up to 50/60 fps with power line frequency 50/60 Hz <b>HDTV 1080p (1920x1080) without WDR:</b> Up to 100/120 fps with power line frequency 50/60 Hz
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264
<b>Image settings</b>	Saturation, contrast, brightness, sharpness, Forensic WDR – 120 dB, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: auto, 0°, 90°, 180°, 270° including corridor format, mirroring of images, dynamic text overlay, image overlay, privacy masks, defogging, noise reduction, electronic image stabilization, barrel distortion correction, orientation aid, fine tuning of behavior at low light Scene profiles: forensic, vivid, traffic overview
<b>Audio</b>	
<b>Audio streaming</b>	Two-way
<b>Audio compression</b>	AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate
<b>Audio input/output</b>	Built-in microphone (can be disabled) External balanced/unbalanced microphone or line input, line output 24 bit AD/DA-conversion
<b>Network</b>	
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP
<b>System integration</b>	
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S and ONVIF Profile G, specifications at <a href="http://www.onvif.org">www.onvif.org</a>
<b>Analytics</b>	<b>Included</b> AXIS Video Motion Detection, active tampering alarm, audio detection, AXIS Fence Guard, AXIS Motion Guard <b>Supported</b>

	AXIS Digital Autotracking, AXIS Perimeter Defender, AXIS Loitering Guard Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>
<b>Event triggers</b>	Analytics, external input, edge storage events Detectors: live stream accessed, video motion detection, audio detection, shock detection Hardware: network, temperature Input Signal: manual trigger, virtual inputs PTZ: error, moving, preset reached, ready Storage: disruption, recording System: system ready Time: recurrence, use schedule
<b>Event actions</b>	File upload: FTP, SFTP, HTTP, HTTPS, network share and email, send video clip Notification: email, HTTP, HTTPS and TCP Overlay text, Send SNMP Trap Video and audio recording to edge storage Pre- and post-alarm video buffering External output activation, day/night vision mode, play audio clip, status LED, WDR mode, Defog mode, PTZ control
<b>Data streaming</b>	Event data
<b>Built-in installation aids</b>	i-CS: Remote zoom and focus Other lens: Remote back focus Traffic wizard, pixel counter, levelling assistant, autorotation
<b>General</b>	
<b>Casing</b>	Metal (zinc) Color lid: Silver – RAL 9006 Color chassis: Black – NCS S 9000-N
<b>Sustainability</b>	PVC free
<b>Memory</b>	1 GB RAM, 512 MB Flash
<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.5 W, max 9.1 W 8–28 V DC, typical 4.3 W, max 9.5 W
<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE I/O: 6-pin 2.5 mm terminal block for four configurable inputs/outputs (12 V DC output, max load 50 mA) RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block 3.5 mm mic/line in, 3.5 mm line out I-CS connector (compatible with P-Iris and DC-iris)
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>
<b>Operating conditions</b>	–20°C to 60°C (–4°F to 140°F) Humidity 10–85% RH (non-condensing)
<b>Storage conditions</b>	–40 °C to 65 °C (–40 °F to 149 °F)
<b>Approvals</b>	<b>EMC</b> EN 55032 Class A, EN 61000–3–2, EN 61000–3–3, EN 55024, EN 61000–6–1, EN 61000–6–2, FCC Part 15 Subpart B Class A, ICES–003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 <b>Safety</b> IEC/EN/UL 62368–1 <b>Environment</b> IEC 60068–2–1, IEC 60068–2–2, IEC 60068–2–6, IEC 60068–2–14, IEC 60068–2–27, IEC 60068–2–78
<b>Dimensions</b>	82 x 66 x 210 mm (3.23 x 2.60 x 8.25 in)
<b>Weight</b>	950 g (2.1 lb)
<b>Included accessories</b>	Stand, connector kit, resistor <sup>®</sup> T20 tool, installation guide, Windows decoder 1-user license
<b>Optional accessories</b>	AXIS T90B Illuminators, Axis network cable couplers, AXIS T8129 PoE Extender, AXIS T8415 Wireless Installation Tool, Axis midspans For more accessories, see <a href="http://www.axis.com">www.axis.com</a>

<b>Video management software</b>	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/support/downloads">www.axis.com/support/downloads</a>	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<a href="http://www.openssl.org/">http://www.openssl.org/</a>), and cryptographic software written by Eric Young (<a href="mailto:ey@cryptsoft.com">ey@cryptsoft.com</a>).</i>
<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	<b>Environmental responsibility:</b>
<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>	<a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>