

# XF40-Q1765 Explosion-Protected Network Camera

Fixed camera for hazardous areas

XF40-Q1765 Explosion-Protected Network Camera is suitable for onshore, offshore, marine and heavy industrial environments. It features a 316L stainless steel housing certified for hazardous areas according to for example ATEX, IECEx and UL. The housing prevents any inside sparks or explosions from escaping and igniting vapors, gases, dust or fibers in the surrounding air. XF40-Q1765 provides superb image quality and color fidelity and a high level of flexible integration with other equipment, such as access control and fire alarms. It offers flexible remote accessibility, using any existing IP-based networks.

- > **Stainless steel (SAE 316L) and impact resistance**
- > **Full HDTV 1080p resolution**
- > **18x zoom and autofocus**
- > **Wide temperature range**



# XF40-Q1765 Explosion-Protected Network Camera

<b>Models</b>	XF40-Q1765 XF40-Q1765 -60 C XF40-Q1765 -50 C UL All models are available in different versions depending on the regional requirements for hazardous equipment certification.	<b>Connectors</b>	XF40-Q1765 models: Three M20 conduit entries XF40-Q1765 UL models: Three 3/4" NPT conduit entries
<b>Certification part code</b>	XF40-Q1765/XF40-Q1765 -60 C: housing 1410-15-00 XF40-Q1765 -50 C UL: housing OXALIS-UL1410-15 All models delivered in 1410-series explosion-protected housing manufactured and certified by Eaton MEDC Ltd., UK.	<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>
<b>Camera</b>		<b>Operating conditions</b>	XF40-Q1765: -40 °C to 70 °C (-40 °F to 158 °F) XF40-Q1765 -60 C: -60 °C to 40 °C (-76 °F to 104 °F) XF40-Q1765 -50 C UL: -50 °C to 70 °C (-58 °F to 158 °F) Humidity 10–100% RH (condensing)
<b>Image sensor</b>	Progressive scan RGB CMOS 1/2.9"	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Lens</b>	4.7–84.6 mm, F1.6–2.8 Horizontal field of view 59°–4° Vertical field of view 35°–2° Autofocus	<b>Approvals</b>	EMC EN 55022 Class A, EN 55024 Class A, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, RCM AS/NZS CISPR 22 Class A Safety EN/UL/CSA 60065 Environment IEC/EN 60529 IP66, IP67, IP68, IEC/EN 62262 IK10 body, IK08 glass Explosion IEC/EN/SANS/ABNT NBR 60079-0, IEC/EN/SANS/ABNT NBR/GOST 60079-1, IEC/EN/SANS/ABNT NBR/GOST 60079-31, GOST 31610.0, GB3836.1, GB3836.2, CAN/CSA-C22.2 No. 60079-0, CAN/CSA-C22.2 No. 60079-1, CSA-C22.2 No. 60065-03, CAN/CSA C22.2 No. 25, CAN/CSA C22.2 No. 30-M, UL 1203
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Certifications</b>	ATEX: II 2 G Ex db IIC T4 Gb -60°C ≤ Ta ≤ +70°C Gb, II 2 D Ex tb IIC T135°C Db IP66/67, Certificate: ITS16ATEX101021X IECEx: Ex db IIC T4 -60°C ≤ Ta ≤ +70°C Gb, Ex tb IIC T135°C Db IP66/67, Certificate: IECEx ITS 15.0068X Inmetro: IIC T4 Gb -60°C ≤ Ta ≤ +70°C Gb, IIC T135°C Db IP66/67, Certificate: UL-BR 17.0063X cLC CSA: Ex d IIC T4 -60°C ≤ Ta ≤ +60°C, Certificate: 11396-1S-CSA EAC: Ex db IIC T4 Gb -60°C ≤ Ta ≤ +70°C, Ex tb IIC T135°C Db IP66/67, Certificate: TCRUCGB.ГБ04.В00587 CCOE: Ex db IIC T4 Gb -60°C ≤ Ta ≤ +70°C, Ex tb IIC T135°C Db IP66/67, Certificate: P400546/1 CNEX: Ex db IIC T4 Gb -60°C ≤ Ta ≤ +70°C, Ex tb IIC T135°C Db IP66/67, Certificate: 17.1235X IA: Ex db IIC T4 Gb -60°C ≤ Ta ≤ +70°C, Ex tb IIC T135°C Db IP66/67, Certificate: S-XPL/17.0244X KCC: Ex d IIC T4 -60°C ≤ Ta ≤ +70°C, Ex tD A21 T135°C IP66/67 -60°C to +65°C, Certificate: 17-GA4B0-0351X, 17-GA4B0-0352X UL: Class I, Division 1, Groups B, C, D, T4+ -50°C to +70°C (-58°F to +158°F), Class II, Division 1, Groups E, F, G, IP67, Class 1 Zone 1 A Ex d IIB + Hydrogen T4, Certificate: 20170721-E477542
<b>Minimum illumination</b>	Color: 0.5 lux at 30 IRE F1.6 B/W: 0.04 lux at 30 IRE F1.6	<b>Dimensions</b>	165 x 176 x 480 mm (6 1/2 x 6 15/16 x 18 7/8 in)
<b>Shutter time</b>	1/28000 s to 2 s	<b>Weight</b>	14 kg (31 lb)
<b>Pan/Tilt/Zoom</b>	18x optical zoom and 12x digital zoom, total 216x zoom 64 preset positions	<b>Included accessories</b>	Sunshield, installation guide, Windows decoder 1-user license, AXIS Surveillance microSDXC™ Card 64 GB
<b>Video</b>		<b>Optional accessories</b>	Ex Power Supply ATEX/IECEx Ex Washer Tank Pressurized ATEX/IECEx, Ex Power Supply UL, Ex Cable ATEX/IECEx/EAC in various lengths, wall and pole stainless steel mounts All accessories are not available for all certifications. For more accessories, see <a href="http://www.axis.com">www.axis.com</a>
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, and Main profiles Motion JPEG	<b>Video management software</b>	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/techsup/software">www.axis.com/techsup/software</a>
<b>Resolution</b>	1920x1080 HDTV 1080p to 160x90	<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
<b>Frame rate</b>	Up to 30/25 fps (60/50 Hz) in all resolutions	<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264	<b>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<a href="http://www.openssl.org">www.openssl.org</a>), and cryptographic software written by Eric Young (<a href="mailto:eyay@cryptsoft.com">eyay@cryptsoft.com</a>).</b>	
<b>Image settings</b>	Compression, color, brightness, sharpness, white balance, exposure control, exposure zones, backlight compensation, WDR – dynamic contrast, fine tuning of behavior at low light, rotation, text and image overlay, day/night shift level	<b>Environmental responsibility:</b> <a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>	
<b>Network</b>			
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, Digest authentication, User access log, Centralized Certificate Management		
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH		
<b>System integration</b>			
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profile S and ONVIF® Profile G, specification at <a href="http://www.onvif.org">www.onvif.org</a>		
<b>Analytics</b>	AXIS Video Motion Detection 4, active tampering alarm Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>		
<b>Event triggers</b>	Analytics, Edge storage events		
<b>Event actions</b>	Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap File upload via FTP, SFTP, HTTP, HTTPS network share and email Notification via email, HTTP, HTTPS and TCP		
<b>Data streaming</b>	Event data		
<b>Built-in installation aids</b>	Pixel counter		
<b>General</b>			
<b>Casing</b>	IP66-, 67-, and 68-rated, electropolished SAE 316L stainless steel casing for maximum corrosion protection		
<b>Memory</b>	256 MB RAM, 128 MB Flash		
<b>Power</b>	Max consumption, 24 V AC: 28 W		