

ES2426-31

24-port 10/100M PoE + 2 Gigabit Copper/SFP Combo Rackmount Web Smart PoE Switch



- 24-Port 10/100Base-TX with PoE + 2-Port Gigabit Copper/SFP Combo Uplink
- IEEE 802.3at PoE+, up to 30W per port
- Maximum 400W power consumption
- Web-based Configuration and Management
- VLAN, QoS, RSTP, IGMP Snooping, LACP, Port Security, Bandwidth Control, Storm Control
- 19" Racmount

Key Features

IEEE 802.3at Power over Ethernet (PoE) ports

ES2426-31 features 24-port PoE+ IEEE 802.3at supplying up to 30 watts per port. This product can convert standard 100~240V/AC power into low-voltage DC that runs over existing LAN cable to power up IEEE 802.3at compliant network accessories. By adding ES2426-31 to existing networking, installing networking products such as Access Points and IP cameras can be easily managed and set up. Wireless device deployments are easily located with available power outlets and network administrators don't need to use heavy AC power adapters anymore.

2 Gigabit Copper/SFP Combo Port

ES2426-31 supports 2 Gigabit Copper or SFP combo ports to uplink to servers, storage, or other switching devices for long loop reach applications.

Exceptionally Smart

The ES2426-31 features management interface that can be managed through Web Browser and it provides Smart features that are ideal for simple network applications and basic monitoring tools to improve network efficiency. Through a Web-based interface, an administrator can set up VLANs to segregate traffic, QoS to prioritize mission-critical data, RSTP/Loop Protection to avoid network loop, link aggregation to create fat traffic pipelines, bandwidth control to limit traffic load and Port Security to secure your network. All of these features offer extra protection on the network edge. Best of all, the password-protected configuration interface can be accessed remotely.



Specifications

Standards	<p>Ethernet: IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.ab 1000BaseT, IEEE 802.3z 1000BaseSX/LX</p> <p>IEEE 802.3x Flow Control</p> <p>IEEE 802.3ad Link Aggregation Control Protocol</p> <p>IEEE 802.1Q VLAN</p> <p>IEEE 802.1p Class of Service</p> <p>IEEE 802.1D Spanning Tree Protocol</p> <p>IEEE 802.1w Rapid Spanning Tree Protocol</p> <p>IEEE 802.3at Power Over Ethernet (PoE+)</p>
Features	<p>Number of Ports: 26</p> <p>10/100BaseTX with RJ-45 Connectors: 24 port with PoE+ Gigabit Uplink: 2x 10/100/1000BaseT RJ-45 / Gigabit SFP Combo Port</p> <p>MAC Address: 4K</p> <p>Buffer Memory: 2.75Mb</p> <p>Transmission Method: Store and Forward</p>
Smart Features	<p>Port Based VLAN: 26</p> <p>Tagged Based VLAN: 32, VID = 1~4094</p> <p>STP/RSTP</p> <p>IGMP Snooping V1&V2</p> <p>Link Aggregation: 3 groups</p> <p>Quality of Service(QoS): High & Low queues, 802.1p</p> <p>Security: Port & MAC binding, 3 MAC per port</p> <p>Port: Port State, Speed/Duplex, Flow Control</p> <p>Port Mirroring</p> <p>Bandwidth Control</p> <p>Broadcast Storm Control</p> <p>PoE Control: PoE Port Enable/Disable, PoE Status</p> <p>Management: Web Management, password protected access, Configuration backup/restore, TFTP firmware upgrade</p>
Filtering/Forwarding Rates	<p>1000Mbps port – 1,488,000pps,</p> <p>100Mbps port - 148,800pps, 10Mbps port - 14,880pps</p>
Transmission Media	<p>10/100BaseTX Cat. 5 UTP/STP</p> <p>1000BaseT Cat. 5 / Cat. 5E UTP/STP</p>
LED Indicators	Per Port: Link/Act, PoE : Act / Status, Per Unit: Power
Power Input	100~240 V/AC, 50~60Hz
Power Output	53V DC Per Port Output
Power Consumption	400 Watt (Max.)
Dimensions	44 × 440 × 332 mm (H x W x D)
Operating Temperature	0 to 40°C
Storage Temperature	-20 to 90°C



Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class A, CE
Weight	4.7kg

