

SC-902D170

2MP H.265 Speed Dome Kamera



Camera	
Sensor	1/1.9 Inch, progressive scan, 2.0 megapixel, CMOS
Lens	6 ~ 180 mm (30x optical zoom) , AF automatic focusing and motorized zoom lens
Shutter	Auto/Manual; shutter time: 1/1 s ~ 1/3, 0000 s
Minimum Illumination	0.001lux (F1.5, 50IRE, Color) 0.0001lux (F1.5, 50IRE, W/B) 0 lux with IR
Iris	Auto/Manual; F1.5 ~ F4.3
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	3D DNR
S/N	>55dB
WDR	DWDR (120dB)
Video	
Video Compression	H.265/H.264BaselineProfile/H.264MainProfile/H.264HighProfile/M-JPEG
Frame Rate	50Hz:25fps(1920×1080), 50fps(1920×1080), 25fps(1280×960), 50fps(1280×960), 25fps(1280×720), 50fps(1280×720) 60Hz:30fps(1920×1080), 60fps(1920×1080), 30fps(1280×960), 60fps(1280×960), 30fps(1280×720), 60fps(1280×720) 50Hz:25fps(704×576), 25fps(352×288) 60Hz:30fps(704×480), 30fps(352×240) 50Hz:25fps(1920×1080), 25fps(1280×960), 25fps(1280×720), 25fps(704×576), 25fps(352×288) 60Hz:30fps(1920×1080), 30fps(1280×960), 30fps(1280×720), 30fps(704×480), 30fps(352×240)
HLC	Supported
BLC	Supported
OSD	Supported
Privacy Mask	Up to 8 areas
Storage	
Edge Storage	Optional Micro SD, up to 128 GB
Network	
Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
Compatible Integration	Onvif, CGI, GB/T28181
Pan & Tilt	
Pan Range	360° (endless)
Pan Speed	0.5°/s ~ 120°/s
Tilt Range	-3° ~ +93°
Tilt Speed	0.5° ~ 100°/s
Number of Presets	255
Patrol	6 patrols, up to 18 presets per patrol
Pattern	4 , with the total recording time not less than 10 mins
Interface	
Network	1RJ45 10M/100M Base-TX Ethernet
CVBS	BNC
communication port	RS485
Infrared	
IR Distance	up to 170meters
IR Intensity	Automatically adjusted. depending on zoom ratio
General	
Power	AC 24V Power consumption: 50W
Mounting temperature	wall mounting; ceiling mounting
Weight	8.7KG (Gross weight)
Working Environment	-30°C ~ +65°C, Humidity:10%~95% RH(non-condensing)
Ingress Protection	IP66 Protection Standard