

# AT-FS750/24POE

## 24 port Fast Ethernet PoE WebSmart Switch



### AT-FS750/24POE-xx

24 port 10/100TX PoE WebSmart switch with 2 SFP combo ports

#### Performance

Allied Telesis' WebSmart switch integrates the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective solution for users to integrate management at the edge of their network. This WebSmart switch provides a network manager some key features using the simple web-based management function such as; port-based VLANs, IEEE 802.1p QoS, port trunking/link aggregation, port mirroring, priority queues and IEEE 802.1x security support. With support of up to 8K MAC addresses and a 512K packet buffer the AT-FS750/24POE WebSmart switch is an ideal option for integrating management into your network solution.

#### Power over Ethernet

Capable of providing up to 12 ports of Class 2 802.3af PoE power (6 ports Class 3), the AT-FS750/24POE is ideally suited for those applications using security cameras, wireless access points, IP phones, and other POE powered devices. The POE option eliminates the need for power rewiring and minimizes the clutter of power supplies and adapters in awkward places.

#### Value

Never thought you could afford managed switches in your network? Always wanted to provide management functionality at the edge? Now's your chance. Allied Telesis' WebSmart switch truly helps network managers get the most value for their dollar. With industry standard protocols, fiber media support via the SFP's, and simple Plug & Play usability right out of the box, how can you go wrong implementing this cost-effective solution into your network?

#### Quality and Reliability

Allied Telesis is a worldwide leader in unmanaged Ethernet switches. Shipping more than 250,000 unmanaged switches each year, Allied Telesis offers proven reliability and industry recognized quality.

#### Key Features

##### VLAN

- IEEE 802.1Q tagged
- Port-based
- Up to 64 groups

##### Quality of Service Classification

- IEEE 802.1p tagging
- Port-based priority
- Four priority queues per port

##### IP Multicast Support (IPv4)

- IGMP snooping(v1/v2)
- Static multicast group

- Spanning-Tree, IEEE 802.1d/w

##### IEEE 802.3ad Link Aggregation

- Manual

##### IEEE 802.1x Port-based and MAC-based Network Access Control

- Local authentication server (MD5 only)
- Remote authentication through RADIUS
- Dynamic VLAN assignment

- RADIUS client for IEEE 802.1x

- DHCP client

- Statistics charts in WEB

##### Others

- IEEE 802.3x flow control or \*HOL blocking prevention (\*when flow control is off)

- Port mirroring

- Destination MAC filtering

- Ingress/egress rate limiting

- Broadcast storming control

#### Management Features

##### Window-based Supporting

- Switch discovery management up to 254 switches
- Monitor list
- Trap view
- Device setting

- Firmware upgrade by FTP and Web

- Configuration backup/restore by FTP

- Factory reset

- Password access control and restricted IP access list

- SNMPv1/v2c

##### MIBs

- RFC 1213 MIB-II
- RFC 1643 Ethernet MIB
- RFC 1493 Bridge MIB
- Private Enterprise MIB (Allied Telesis provide the spec)

##### RMON Groups (1,2,3,9)

- Stats
- History
- Alarms
- Events

#### PoE Intelligent Management

- IEEE 802.3af standard
- 12 10/100TX ports support PoE function (ports 1 to 12)
- Support up to 6 10/100TX ports in 15.4W simultaneously
- PoE module function tests
- Per-port LED/status monitoring
- Automatic detection and power budgeting

# AT-FS750/24POE | 24 port Fast Ethernet PoE WebSmart Switch

## Performance

14,880pps for 10Mbps Ethernet  
148,800pps for 100Mbps Ethernet  
1,488,000pps for 1000Mbps Ethernet

MAC addresses	8K
Packet buffer	512KB
DRAM	32M
Flash	4M

## Power Characteristics

Voltage	90-240V AC
Frequency	50/60Hz
PoE	100W, 48vDC

## Interface Connections

10/100	RJ-45
SFP	1000SX or 1000LX

## Environmental Specifications

Operating temp.	0°C to 40°C (32°F to 104°F)
Non-operating temp.	-25°C to 70°C (-13°F to 158°F)
Operating humidity	5% to 90% non-condensing
Storage humidity	5% to 95% non-condensing
Vibration	IEC 68-2-36
Shock	IEC 68-2-29
Drop	IEC 68-2-32

## Technical Specifications

### Physical Characteristics

Dimensions 44.4cm x 32.2cm x 4.35cm  
17.5" x 12.7" x 1.7"

Weight 4.13 kg (9.11 lbs)

### Wall-mount or Desktop

All units come with wall / 19" rack-mount brackets

## Standards and Compliance

IEEE 802.3	CSMA/CD
IEEE 802.3i	10T
IEEE 802.3u	100TX
IEEE 802.3z	1000SX/LX
IEEE 802.3z/ab	1000T
IEEE 802.3x	Flow control
IEEE 802.1p	Prioritization (four queues)
IEEE 802.1x	Authentication
IEEE E802.1d	Bridging
IEEE 802.3ad	Link aggregation
IEEE 802.1Q	Tagged VLAN
IEEE 802.1d/w	Spanning-Tree
	Rapid Spanning-Tree
IEEE802.3af	PoE

## Electrical/Mechanical Approvals

UL 1950  
FCC/EN55022 Class A  
VCCI Class A  
C-Tick  
EN60950 (TUV)  
EN55024  
CE  
CSA / CUL

## MTBF

256,000 hours  
Bellcore TR332

## Ordering Information

### AT-FS750/24POE-xx

24 port 10/100TX PoE Websmart switch  
with 2 SFP combo ports

Where xx =	10 for US power cord
	20 for no power cord
	30 for UK power cord
	40 for Australian power cord
	50 for European power cord

## Product Contents

Switch unit  
Rack-mount/wall-mount brackets and screws  
Power cord  
User manual/install guide on CD  
Rubber feet

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

[www.alliedtelesis.com](http://www.alliedtelesis.com)

© 2007 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000215 Rev. D