



Specification Highlight

Model	AVerDiGi SF1311H-DV (Vandal Proof Dome Type)
Device	1/4 inch progressive CMOS
F/No	F1.2
Focus Length	f2.7mm-9mm
Effective Pixels	1280 x 1024 pixels
Sensitivity	0 Lux @ F1.2 (IR LED on)
Signal to Noise	bETTER THAN 44dB
Pan & Tilt Control	RS-485
ICR	Yes (Auto, Manual, Scheduler, Delay time)

Video Encoder	H.264, MPEG4 and Motion JPEG simultaneously
Video Profile	13 profiles simultaneously
Frame Rate	Up to 15fps at magapixel mode (1280x1024) ; Up to 30fps at VGA mode (640x480)
Streaming	Simultaneously multi-profile streaming ; Streaming over UDP, TCP, or HTTP ; M-JPEG streaming over HTTP ; Supports 3GPP mobile surveillance ; Controllable frame rate and bandwidth ; CBR/VBR (MPEG4/H.264)
Audio Encoder	G.711/G.726/AMR(3GPP)
Audio Streaming	Two way audio
Microphone	External microphone input
Protocols	TCP, UDP, HTTP, SMTP, FTP, NTP, DNS, DDNS, DHCP, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, PPPoE, 3GPP, ICMP, SAMBA
Security	Password protection, IP address filtering, user access log
Users	Max. 20 users simultaneously
Ethernet	10/100M
DI/DO	1/1
Power Supply	DC 12V 1A
Power Consumption	5W (max) / 6W (max) while IR LED on
POE	IEEE 802.3af
IR LED	24pcs IR LED (around 15-20M distance)
Temperature and Humidity	-10°C to 50°C , 20% ~ 80% humidity (Operating)
Indoor/Outdoor	Indoor/Outdoor (IP66)
OS	Windows XP, Vista, Windows7
Browser	IE 6.0 or above / Firefox 2.0 or above / Safari
Player	3GPP, VLC, Quick Time, Real Player, Coreplayer
Dimensions (W x H x D)	145x108x145 (mm)
Weight	1165g