

DP-22CD2512F-I(S)

1.3MP Mini Sabit Lensli Network Kamera



Genel Özellikler

- 1.3 megapiksel (1280 x 960) çözünürlük
- HD real-time video
- -I: IR LED (10m'ye kadar aydınlatma)
- DWDR & 3D DNR & BLC
- Dahili Depolama (64 GB'a kadar)
- -S: Ses I/O, Alarm I/O
- IP66 koruma
- Darbeye dayanıklı muhafaza

Özellikler

DP-22CD2512F-I(S)	
Camera	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.19 lux@F2.0, AGC on
Shutter time	1/30s ~ 1/100,000s
Lens	4mm@F2.0, angle of view: 75.8° (2.8mm, 6mm optional)
Lens mount	M12
Day & night	ICR
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
Backlight compensation	Yes, zone configurable
Compression standard	
Video compression	H.264 / MJPEG H.264 compression profile
H.264 compression profile	Main profile Main Profile
Bit rate	32 Kbps ~ 16 Mbps
Image	
Max. image resolution	1280 x 960
Frame rate	60Hz: 30fps (1280 x 960), 30fps (1280 x 720)
Image settings	Saturation, brightness, contrast adjustable through client software or web browser
Network	
Network storage	NAS
Alarm trigger	
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP,
System compatibility	ONVIF, PSIA, CGI
General functionalities	Flickerless, dual stream, heartbeat, mirror, user authentication, video mask,
Interface	
Communication interface	1 RJ45 10M / 100M ethernet port
On-board storage	Built-in Micro SD card slot, up to 64 GB
General	
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)
Power supply	DC12V ± 10%, PoE (802.3af)
Power consumption	Max. 7W
Impact protection	IEC60068-2-75Eh, 50J; EN50102, up to IK10
Ingress protection level	IP66
IR range	Up to 10m
Dimensions	99.9 × 97.5 × 46.5 mm (3.93" × 3.84" × 1.83")
Weight	250g (0.55 lbs)