

DP-22TD2366-100 **Thermal Network Bullet Camera**



DeepinView^{series}



Dunlop DP-22TD2366-100 Thermal Network Bullet Camera is applied to perimeter defense and fire-prevention purposes in critical infrastructures such as: airport, railway, prison, power station, 4S stores, and so on. The pre-alarm system helps you discover unexpected events immediately and protects you from property loss.

Smart Function (Thermal Imaging)

- Leading image processing technology: Adaptive AGC, DDE, 3D DNR, NETD less than 40mk (@25°C, F#=1.0)
- Powerful behavior analysis function, based on deep learning algorithm: Line crossing, Intrusion, Region Entrance & Exit
- Reliable temperature exception alarm function
- Advanced fire detection algorithm

Thermal Imaging Module Function

- 640 × 512 resolution sensor, high sensitivity sensor, support contrast adjustment
- Shutter adjustment in various modes
- 3D DNR, 15 palettes of color adjustable, image detail enhancement

Specifications

| Thermal Module | |
|------------------------------|--|
| Image Sensor | Vanadium Oxide Uncooled Focal Plane Arrays |
| Max. Resolution | 640 × 512 |
| Pixel Interval | 17 μm |
| Response Waveband | 8 μm to 14 μm |
| NETD | less than 40mk (@25°C,F#=1.0) |
| Lens (Focal Length) | 100 mm |
| MRAD | 0.17 mrad |
| Field of View | 6.23° × 4.98° (H × V) |
| Min. Focusing Distance | 10 m |
| Aperture | F 1.0 |
| Smart Function | |
| VCA (Video Content Analysis) | 4 VCA rule types (Line Crossing, Intrusion, Region Entrance, and Region Exiting), up to 8 VCA rules. |
| Temperature Measurement | 3 temperature measurement rule types, 21 rules (10 points, 10 regions, and 1 line). |
| Temperature Range | -20 °C to 150 °C (-4 °C to 302 °F) |
| Temperature Accuracy | ± 8 °C (14.4 °F) |
| Fire detection | Dynamic fire point detection, up to 10 fire points detectable. |
| Network | |
| Main Stream | 50fps (640×512, 384×288, 352×288) |
| Sub Stream | 50fps (640×512, 384×288, 352×288) |
| Third Stream | 50fps (640×512, 384×288, 352×288) |
| Video Compression | H.265/H.264/MJPEG, H.265+/H.264+ encoding with Baseline/Main/High Profile |
| Audio Compression | G .711u/G.711a/G.722.1/MP2L2/G.726/PCM |
| Protocols | IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS,NTP, RTSP, RTCP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour |
| Simultaneous Live View | Up to 20 |
| User/Host level | Up to 32 users, 3 levels: Administrator, Operator, User |
| Security Measures | User authentication (ID and PW), MAC address binding, HTTPS encryption, IEEE 802.1x access control, IP address filtering |
| Integration | |
| Alarm Input | 2-ch inputs (0-5V DC) |
| Alarm Output | 2-ch relay outputs, alarm response actions configurable |
| Alarm Action | Preset/Patrol Scan/Pattern Scan/SD Card Record/Relay Output/Smart capture/FTP upload/Email linkage |
| Audio Input | 1 3.5mm Mic in/Line in interface. Line input: 2-2.4V[p-p], output impedance:1KΩ±10% |

| Integration | |
|------------------------------|--|
| Audio Output | Linear Level; Impedance: 600Ω |
| Ethernet | 1 RJ45 10M/100M Self-adaptive Ethernet interface |
| SD Memory Card | Built-in Micro SD card slot, support Micro SD/SDHC/SDXC card (up to 64G), support manual/alarm recording |
| Analog Video Output | 1.0V [p-p]/75Ω, PAL/NTSC/BNC |
| Application Programming | Open-ended API, support ISAPI, HIKVISION SDK and third-party management platform |
| Client | iVMS-4200 |
| Web Browser | IE9+, chrome31-chrome44, Firefox 30-Firefox51, Safari 5.02+(mac) |
| General | |
| Menu language | English |
| Power | 24 VAC± 25%, 12 VDC± 20%, two-core terminal block PoE (802.3at, class 4) |
| Power Consumption | 24 VAC± 25%: 0.92 A, 12 VDC ± 20%: 1.9 A, max. 8W (22W with De-icing Heater On), PoE (802.3at, class 4): 42.5 V to 57 V, 0.4 A to 0.5 A |
| Working Temperature/Humidity | -40 °C to 65 °C (-40 °F to 149 °F), 90% or less |
| Protection Level | IP66 Standard TVS 6000V Lightning protection, surge protection, voltage transient protection |
| Dimensions | 535mm × 400mm × 171mm (21.06" × 15.75" × 6.73") |
| Weight | Approx. 6.40 kg (14.11 lb) |