

Dynacom DN3304P SERIES 16CH NVR



- 16 channel input
- Support H.265/H.264 video formats
- Support 2-ch HDMI, 1-ch VGA, HDMI2 at up to 4K(3840x2160) resolution
- 4 SATA HDDs, Up to 8TB for each HDD



Model Number	Dynacom DN3304P
IP Video Input	16-ch
Two-way Audio Input	1-ch, RCA
Incoming Bandwidth	160Mbps
Outgoing Bandwidth	320Mbps
Remote Users	128
HDMI/VGA output	<p>HDMI1/VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz</p> <p>HDMI2: 4K (3840x2160) /60Hz, 4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz</p>
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Synchronous Playback	16-ch
Compression	H.265/H.264
Live view/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	4 x 12MP@20, 4 x 4K@30, 8 x 4MP@20, 16 x 1080p@25, 32 x 720p@25
SATA	4 SATA interfaces
Capacity	up to 8TB for each HDD
Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
Serial Interface	1 x RS485
USB Interface	<p>Front panel: 2 x USB2.0</p> <p>Rear panel: 1 x USB3.0</p>
Alarm In	16-ch
Alarm Out	4-ch
Power Output	12 VDC
Max Power	<p>Max 30W for single port</p> <p>Max 200W in total (12.5W for each)</p>
Supported Standard	IEEE 802.3at
Power Supply	100 ~ 240 VAC
Consumption (without HDD)	≤ 20 W
Working Temperature	-10°C ~ + 55°C (+14°F ~ +131°F)