



## Dynacom WQ4240PT 40X Network PTZ camera

- 1/2.8" SONY Exmor CMOS Sensor
- 1920x1080
- Multiple Streams
- 40x Optical Zoom
- Pan: 0°~360°,Tilt: +40° ~-70°
- Color 0.1Lux; B&W 0.002Lux
- Defog, Flip, WDR,ICR
- IP66

CAMERA	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. illumination	Color 0.1Lux; B&W 0.002Lux
Day & Night	ICR
Shutter Speed	1/25-1/10000s
S/N	>50dB
White Balance	ATW1/ATW2/PUSH
Lens	40X Optical Zoom ,F=7.75mm(F1.6)~310mm(F5.6)
FOV	55.5°×3.0°(H)
Pan/Tilt	Pan: 0°~360°,Tilt: +40° ~-70°
Pan/Tilt Speed	Pan:0.1°~80°/s ,Tilt:0.1°~60°/s ;
Preset/Tour/Scan/Track	256/ Yes/ Yes/ Yes
IR LED	N/A
IR Range	N/A
IMAGE	
Video Compression	H.264 BP/MP/HP,MJPEG
Bit Rate (CBR/VBR)	500Kb~10Mb
Audio Compression	G.711 ,RAW_PCM,NONE
Max.Resolution	1920x1080/30fps
Stream	Stream1 1920x1080, Stream 2 D1/CIF
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
Special function	DeFog/Flip/WD
Image Overturn	Horizontal /Vertical /Horizontal+Vertical
NETWORK	
Network Protocols	IPv4/v6,RTSP/RTP/RTCP,TCP/UDP,HTTP,DHCP,DNS,FTP,DDNS,PPPOE,SMTP,SIP
Alarm Trigger	N/A
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player.
Security	User security authentication, Reset, Hardware Watch Dog
Web Language	English, Chinese
System Compatibility	Onvif
INTERFACE	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio I/O	N/A
Alarm I/O	N/A
RS485	Yes
BNC Output	Yes

Reset Button	N/A
Edge Storage	Micro SD/SDHC slot (Built-in),Max 32GB
<b>GENERAL</b>	
Power Supply	AC24V±10%
Power Consumption	30W
OperatingTemperature	-25 °C ~ 55 °C (-13 °F ~ 131 °F)
Ingress Protection	IP66
Approvals	CE / FCC
Product Dimensions	345x202x445mm
Product Weight	10kg

### Dimension

