



## DS-2CD2010-I 1.3MP IR Mini Bullet Camera



### Key features

- 1.3 megapixel high resolution
- HD real-time video
- 3D DNR & DWDR & BLC
- IR LEDs: up to 30m
- IP66
- PoE
- Compact design

### Dimensions



DS-2CD2010-I	
<b>Camera</b>	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @F1.2, AGC ON, 0 lux with IR
Shutter time	1/25s (1/30s) ~ 1/100,000s
Lens	4mm @F2.0, angle of view: 69.4° (6mm, 12mm optional)
Lens mount	M12
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
<b>Compression Standard</b>	
Video compression	H.264 / MJPEG
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Dual stream	Yes
<b>Image</b>	
Max. Image Resolution	1280 × 960
Frame rate	50Hz: 25fps (1280 × 960), 25fps (1280 × 720), 25fps (704 × 576), 25fps (640 × 480) 60Hz: 30fps (1280 × 960), 30fps (1280 × 720), 30fps (704 × 576), 30fps (640 × 480)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
<b>Network</b>	
Network storage	NAS (iSCSI optional)
Alarm trigger	motion detection, tampering alarm
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour (SIP optional)
Interoperability	ONVIF, PSIA, CGI
Security	User Authentication, watermark, reset button
<b>Interface</b>	
Communication interface	1 RJ45 10 M / 100 M Ethernet interface
<b>General</b>	
Operating conditions	-30 °C ~ 60 °C (-22°F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	max. 5W (max. 7W with ICR on)
Weather proof rating	IP66
IR range	Up to 30m
Dimension	60.4 x 76.9 x 139.2mm
Weight	500g (1.1 lbs)

### Available model

DS-2CD2010-I

\* Product picture and technical specs subject to change without previous notice. For further information, please contact our local sales team.