

JVC®

1/3" CCD COLOR VIDEO CAMERA

TK-T2101RU
TK-T8101WPRU

LoLux™



TK-T8101WPRU



TK-T2101RU

IR LoLux Security Cameras

Powerful new infrared camera range



TK-T8101WPRU

TK-T2101RU


- 1/3" CCD high-resolution camera with 10-bit DSP
- 600 TVL horizontal resolution
- LoLux™ sensitivity: 0.05 lux color, 0 lux with IR LED
- Varifocal lens included (dome: 2.8 – 10.5mm, bullet: 3.3 – 12mm)
- Automatic High Light Compensation for extreme white light
- Easy wide dynamic range function for backlight compensation
- Built-in motion detection and privacy mask areas
- Ultra-compact design (dome)
- Dust and waterproof IP66 rated for outdoor installation (bullet)
- 24VAC / 12VDC power supply

Specifications


	TK-T2101RU	TK-T8101WPRU
		
Camera		
Signal system	NTSC	NTSC
Image device	1/3 type High-resolution IT CCD	1/3 type High-resolution IT CCD
Effective pixels	480,000 (976H x 494V)	480,000 (976H x 494V)
Scanning system	2:1 Interlace V: 60 Hz, H: 15.625 KHz	2:1 Interlace V: 60 Hz, H: 15.625 KHz
Sync system	Internal	Internal
Video output	Composite video signal: 1.0V (p-p), 75 ohms (BNC)	Composite video signal: 1.0V (p-p), 75 ohms (BNC)
Video S/N ratio	50 dB	50 dB
Horizontal resolution	600 TV lines	600 TV lines
Minimum illumination (typical)	0.05 lx (50%, F1.2) 0.025 lx (25%, F1.2)	0.05 lx (50%, F1.4) 0.025 lx (25%, F1.4)
B&W mode	0.015 lx (50%, F1.2) 0 lx (with IR LED ON)	0.015 lx (50%, F1.4) 0 lx (with IR LED ON)
Iris control	DC iris	DC iris
White balance	ATW / Manual / User / Push / Push lock	ATW / Manual / User / Push / Push lock
Shutter speed	1/60 to 1/10,000	1/60 to 1/10,000
Day/Night	True D/N with IR cut-off filter	True D/N with IR cut-off filter
Digital noise reduction	YES	YES
BLC	OFF / BLC / HLC	OFF / BLC / HLC
AGC	AUTO / MANUAL	AUTO / MANUAL
Motion detect	4 areas	4 areas
Privacy mask	Max. 8 areas	Max. 8 areas
IR LED	14 LEDs	28 LEDs
IR wavelength	850 nm	850 nm
IR distance	15M	20M
On screen menu	English, French, German, Spanish, Russia, Portuguese, Simplified Chinese, Japanese	English, French, German, Spanish, Russia, Portuguese, Simplified Chinese, Japanese
Lens		
Focal length	2.8mm to 10.5mm, 3.75x vari-focal [100(H) x 73(V) to 24(H) x 21(V)]	3.3mm to 12mm [100(H) x 73(V) to 24(H) x 21(V)]
View angle	Horizontal: 101.8 (wide) to 27.4 (tele) degrees Vertical: 73.7 (wide) to 20.6 (tele) degrees	Horizontal: 89.8 (wide) to 23.9 (tele) degrees Vertical: 63.6 (wide) to 17.9 (tele) degrees
Aperture ratio	F1.2	F1.4
General		
Power supply	24VAC (50Hz/60Hz) / 12VDC	24VAC (50Hz/60Hz) / 12VDC
Power consumption	5W	7W
Operating temperature range	14°F to 122°F (-10°C to 50°C)	14°F to 122°F (-10°C to 50°C)
Dust and water proof	-	IP66
Vandal protection	-	Vandal protected
Dimensions	φ 4.41" x 3.82" (112 mm x 97 mm)	φ 3.26" x 8" (83 mm x 206 mm)
Weight (approx.)	0.67 lb (300 g)	1.49 lb (680 g)

Dimensions

Unit: Inch (mm)



TK-T2101RU



TK-T8101WPRU

All brand or product names may be trademarks and/or registered trademarks of their respective owners.
Copyright © 2012, JVC KENWOOD Corporation

JVC®

DISTRIBUTED BY

Design and specifications subject to change without notice.

