



2.0 Megapixel HD AHD IR Bullet Camera OAL-62IRAHD

| Model No. | OAL-62IRAHD |
|-------------------------------------|--|
| Sensor | 1/3" 2.0 Mega Pixel Sony CMOS |
| Min.Illumination | 0.06Lux @(F1.2,AGC ON) ,0 Lux with IR |
| Shutter time | 1/25s ~ 1/100,000s |
| S/N (Y signal) | 52dB (AGC Off, Weight On) |
| Image Resolution | 1080P (1920x1080P) |
| Frame Rate | 30 fps (60 Hz), 25fps (50Hz) |
| Minimum Illumination | 0.01Lux |
| Day/Night Mode | ICR-IR cut filter |
| Number of IR LEDs | 12pcs IR LED Laser |
| Infrared Illumination(Night Vision) | Visible up to 196' (60m) |
| Lens Mount | 2.8-12mm |
| Backlight Compensation | BLC/HLC, backlighting setup, off |
| White Balance | Auto, Manual, Fluorescent light, Incandescent lamp, Sunlight, Flash lamp, Cloudy and Shadowy |
| DNR | 3D-DNR |
| Transmission Distance | Over 500m via 75-3 coaxial cable |
| Video Output | 1ch AHD (1.0Vp-p, 75Ω), remote storage at IE client |
| Power | 12V DC |
| Power Consumption | 350mA (IR on max 650mA) |
| Operating Temperature | -10~ +50 Deg C. RH 95% Max. |
| Storage Temperature | -20~ +60 Deg C. RH 95% Max. |
| Waterproof | Yes |
| Video Out | 1.0V p-p 75Ω, BNC Connector |
| Dimensions(WxDxH) | 268.7mmx108.4mmx89.9mm |
| Weight | 780g |
| Material | Aluminum Alloy |

