

# 8Channel OAR-3108AHD

## AHD/NVR/DVR Three-in-one AHD



### Key features

- H.264 Video compression
- AHD/NVR/DVR Three-in-one
- Support multi-mode switch
- AHD: 8CH\*720P
- Analog: 8CH\*960H
- AHD+Analog:4CH\*720P+4CH\*960H
- IPC: 8CH\*720P
- Playback resolution:4CH AHD 720P@100fps 8ch D1@200/240fps
- Synchronous palyback : D1/CIF/720P/960P

### Rear Panel of OAR-3108AHD



1. Video input
2. Video output
3. VGA interface
4. Audio in
5. LAN network interface
6. HDMI interface
7. USB interface
8. RS-485
9. DC 12V

MODEL	OAR-3108AHD
Video/Audio input	
Video compression	H.264
Analog video input	8PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Audio compression	ADPCM
Audio input	4PCS RCA Port(Level : 2.0Vp-p, impedance : 1kΩ)
Two-way audio input	1PCS RCA Port( line level , impedance : 1kΩ)
Video/Audio output	
HDMI/VGA output	1024x768,1280*720,1280x1024
Encoding resolution	D1/CIF/720P/960P
Multi-mode switch	AHD: 8CH*720P Analog: 8CH*960H AHD+Analog:4CH*720P+4CH*960H IPC: 8CH*720P
CVBS output	1PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Frame rate	NTSC : 1~30FPS/S ; PAL : 1~25FPS/S
Video bit rate	256KB/384KB/512KB/640KB/768KB/1MB/1.5MB/2MB/2.5MB/3MB/4MB/5MB/6MB/8MB
Audio output	1PCS RCA Port( line level , impedance : 1kΩ)
Audio bit rate	16kpbs
Dual-stream	YES
Stream type	combine streams/ video stream
Playback resolution	4CH AHD 720P@100fps 8ch D1@200/240fps
Synchronous palyback	D1/CIF/720P/960P
Hard disk	
SATA	1*SATA
eSATA	No
Capacity	each port support max 4TB HDD
External interface	
Network interface	1PCS RJ45 10M / 100M adaptive Ethernet port
Serial interface	1PCS RS485
USB interface	2*USB2.0
Alarm in/out	NO
General	
Power supply	DC12V
Comsumption	≤12W
Working temperature	-10°C--+55°C
Working humidity	10%--90%
Chassis	0.8U
Dmensions(W×D×H)	255*215*45mm
Weight	0.86kg

