

OAR-6408AHD 8CH 1080P AHD DVR

AHD/NVR/DVR Three-in-one AHD



Key features

- H.264 Video compression
- AHD/NVR/DVR Three-in-one
- Support multi-mode switch
- AHD: 8CH*1080P(compatible with 720P)
- AHD+IP: 8CH*720P+4CH*IPC1080P;
- IP: 16CH*1080P; 4CH*5M;
- Synchronous palyback : 1/4/9/16CH

Rear Panel of OAR-648AHD



1. Audio in
2. Video in
3. LAN network interface
4. Power switch
5. DC 12V
6. RS-485
7. Alarm out
8. Alarm In
9. USB interface
10. VGA interface
11. HDMI interface

MODEL	OAR-6408AHD
Video/Audio input	
Video compression	H.264
Analog video input	8PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Audio compression	ADPCM
Audio input	8PCS RCA Port(Level : 2.0Vp-p, impedance : 1kΩ)
Two-way audio input	1PCS RCA Port(line level , impedance : 1kΩ)
Video/Audio output	
Multi-mode switch	AHD: 8CH*1080P(compatible with 720P) AHD+IP: 8CH*720P+4CH*IPC1080P; IP: 16CH*1080P; 4CH*5M;
HDMI/VGA output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
CVBS output	NO
Encording resolution	CIF/D1/960H/720P/960P/1080P/3M/5M
Frame rate	NTSC : 1~30FPS/S ; PAL : 1~25FPS/S
Video bit rate	256kps/384Kbps/512Kbps/640kbps/768Kbps/1M/1.5M/2M/2.5M/3M/4M/5M/6M/8M
Audio output	1PCS RCA Port(line level , impedance : 1kΩ)
Audio bit rate	16kpbs
Dual-stream	YES
Stream type	combine streams/ video stream
Playback resolution	4CH*1080P^76FPS,8CH*720P^200FPS,8CH*720P^200FPS+4CH*1080P^100FPS,4CH*5M^40FPS (It is defined with the mode switch)
Synchronous palyback	CIF/D1/960H/720P/960P/1080P/3M/5M
Hard disk	
SATA	4*SATA
eSATA	No
Capacity	each port support max 4TB HDD
External interface	
Network interface	1PCS RJ45 10M / 100M/1000M adaptive Ethernet port
Serial interface	1PCS RS485
USB interface	2*USB2.0
Alarm in/out	4
General	
Power supply	DC12V
Consumption	≤24W
Working temperature	-10°C-- +55°C
Working humidity	10%--90%
Chassis	1.5U
Dmensions(W×D×H)	430*365*68mm
Weight	5KG