

T Series IP Camera

OND-T3610



Series	T Series 2MP, H.264+, 3.6mm Fixed Lens, Digital WDR, Dome Type
---------------	---

Camera

Image Sensor	1 / 2.8 "CMOS
Image Size	1920 x 1080
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Auto Iris	Fixed Iris
Min. Illumination	0.05 lux @F1.2,AGC ON; 0 lux with IR
Lens	3.6 mm @ F1.6, angle of view: 79° (OND-T3610-1 model 2.8 mm)
Lens Mount	M12
Day & Night	ICR
Wide Dynamic Range	Digital WDR
Digital NR	3D DNR
Angle Adjustment	Any angle

Image

Video Compression	H.264+ / MJPEG
H.264 Compression	Baseline Profile / Main Profile / High Profile
Resolution	1080P (1920 x 1080), 720P (1280 x 720),D1, CIF, 480 x 240
Main Stream	60Hz : 1080P (1 ~ 30 fps) / 720P (1 ~ 30 fps) 50Hz : 1080P (1 ~ 25 fps) / 720P (1 ~ 25 fps)
Bit Rate	256 Kbps ~ 5 Mbps
Encode Mode	VBR / CBR
Quality	Five levels under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, sharpen, NR, etc. adjustable through client software or web browser
ROI	3 ROI

Interfaces

Network	RJ45
----------------	------

Functions

Remote Monitoring	IE browsing,CMS remote control
Online Connection	Support simultaneous monitoring for up to 3 users ; Support multi-stream real time transmission
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, DDNS, SMTP,FTP
Interface Protocol	ONVIF
Storage	Network remote storage
Smart Alarm	Motion alarm
PoE	Yes
IR Distance	10 ~ 20m
Water-proof	IP66,IK10

Others

Power Supply	DC12V / PoE
Power Consumption	< 2W
IR Consumption ON	< 4W
Operating Environment	- 20 °C ~ 50 °C, 10 % ~ 90 % relative humidity
Dimensions (mm)	Ø87 x 108
Weight (net)	369g
Installation	Pendent mounting

2 MP Network IR Water-proof Dome Camera



Features

- * 2MP (1920 x 1080) full real time coding
- * Max. resolution: 1920 x 1080
- * ICR auto switch, true day / night
- * 10 ~ 20m IR night view distance
- * 3D DNR, digital WDR
- * ROI coding
- * PoE power supply optional
- * Support smart phone, iPad, remote monitoring
- * Support P2P
- * IP66 ingress protection
- * Support three streams

