

PTZ Dome Camera

ONP-P37201-RH



3 MP Network IR HD Pan Tilt Zoom Dome Camera



Series	X Series 3MP, H.265, PTZ Dome
---------------	----------------------------------

Camera

Image Sensor	1 / 2.8" Progressive CMOS
Effective Pixels	2048 x 1536 3Mega
Horizontal Resolution	1200 TVL
Min.Illumination	0 Lux
IR Distance	100 m
White Balance	Auto / Manual
S / N Ratio	Max 48dB
Day / Light	Auto / Manual
Focus Mode	Auto / Manual
Lens	20x Zoom, f = 5.5 ~ 110 mm, F1.6 ~ F3.5

PTZ

Pan Range	360° endless rotation
Pan Speed	Preset speed : 240 °/s; Manual control speed : 0.5 ~ 90 °/s
Tilt Range	0 ~ 93° (auto rotation)
Tilt Speed	Preset speed : 160 °/s; Manual control speed : 0.5 ~ 90 °/s

System

PTZ Control	Yes
Preset	255
Cruse	8
Track	4
Time Task	8
Scan	2
Home Position	Yes
Auto Flip	Yes
OSD Menu	English
Alarm Input	1
Alarm Output	1
Alarm Linkage	Yes

Network

Compression	H.265
Frame Rate	1 ~ 30fps (25 fps)
Protocol	TCP / IP, UDP, DHCP, DDNS, NTP, RTSP, SMTP, FTP, PPPoE
Storage	SD card local storage, network remote storage
Smart Alarm	Motion Alarm, Sensor Alarm
Resolution	3MP (2048 x 1536), 1080P (1920 x 1080), 720P (1280 x 720), D1, CIF, 480 x 240
Multi-stream	Yes

Port

Network Interface	10 Base-T / 100 Base-TX, RJ45
Audio	MIC input x 1, MIC output x 1

Others

Control	Network
Power Supply	AC 24V / 3000 mA
Power Consumption	15 W (max 30W, IR on)
Working Environment	Temperature : - 30 °C ~ 60 °C; Humidity : less than 95%
Protection Level	IP66; TVS 6KV lightning protection, surge protection
Weight	3.5KG
Dimensions (mm)	Φ 209 x 317

Features

- 3MP (2048 x 1536) resolution (real time)
- 1/2.8" CMOS Progressive scan
- H265 codec
- TCP/IP, UDP, DHCP, DDNS, NTP, RTSP, SMTP, FTP, PPPoE
- x20 Motorized Zoom Lens
- Day/Night
- Infrared Cut Filter (ICR)
- SD Card local/remote storage
- Motion Alarm, Sensor Alarm
- Multi streams support
- Two-way audio connection
- Up to 100 meter IR Distance
- IP66 protection
- TVS 6KV Lightning /surge protection

