

SN-ADR2208E1

1080P 8CH 1HDD Hybrid DVR



Specifications

VIDEO	
Video Compression	H.264 High Profile
Encode Ability	8ch*1080P@12fps
Decode Ability	8ch*1080P@12fps
Video Input	Pure Analog:8ch*1080P@30fps Mixed Input:8ch*1080P(Analog + IP), Pure Network:8ch*1080P/3MP/5MP;
AUDIO	
Audio Compression	G711A
Two Way Audio	Support
RECORD AND PLAYBACK	
Hard Drive	1 SATA(Each maximum support 6T)
Record	Manual/Event/Timer
Playback	8ch(pure local input mode)
STORAGE AND BACKUP	
Space Occupation	960H:12~20G/ day*channel
	720P:10~20G/ day*channel
	1080P: 20~30G/ day*channel
	Audio:691.2M/ day*channel
Backup Mode	USB HDD
INTERFACE	
Video Input	8ch BNC (AHD/TVI/CVI/CVBS)
Video Output	1ch VGA,1ch HDMI,1ch CVBS
Audio Input	4ch RCA
Audio Output	1ch RCA
Alarm Input	N/A
Alarm Output	N/A
Network Interface	1 RJ45 10M/100M Adaptive Ethernet Port
PTZ Control	RS485, Support Multiple PTZ Protocols
USB	2 USB
Hard Disk	1 SATA
GENERAL	
Power	DC12V/2A
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Dimension	255mm(L)x 255mm(W)x 45mm(H)
Product Weight	1100g

Key features

- Support AHD/TVI/CVI 1080P series front-end real-time encoding;
- Support VGA, ,CVBS,HDMI 1080P HD output;
- Support InviewPro3 Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (Firefox, IE) ;
- Support more than languages, no nation boundaries;
- Perfect protection circuit, unique triple watchdog function
- Supporting web, IMS, provide SDK development

Interface:



Dimension:

