

SN-ADR2216E2

1080P 16CH 2HDD Hybrid DVR



Specifications

VIDEO	
Video Compression	H.264 High Profile
Encode Ability	16ch*1080P@12fps
Decode Ability	16ch*1080P@12fps
Video Input	Pure Analog: 16ch*1080P@30fps Mixed Input: 16ch*1080P(Analog + IP), Pure Network: 16ch*1080P/3MP/5MP
AUDEO	
Audio Compression	G711A
Two Way Audio	Support
RECORD AND PLAYBACK	
Hard Drive	2 SATA(Each maximum support 6T)
Record	Manual/Event/Timer
Playback	16ch(pure local input mode)
STORAGE AND BACKUP	
Space Occupation	960H:12~20G/ day*channel
	720P:10~20G/ day*channel
	1080P 20~30G/ day*channel
	Audio:691.2M/ day*channel
Backup Mode	USB HDD
INTERFACE	
Video Input	16ch BNC (AHD/TVI/CVI/CVBS)
Video Output	1ch VGA,1ch HDMI,1ch CVBS
Audio Input	6ch RCA
Audio Output	1ch RCA
Alarm Input	4ch
Alarm Output	1ch
Network Interface	1 RJ45 10M/100M Adaptive Ethernet Port
PTZ Control	RS485, Support Multiple PTZ Protocols
USB	2 USB
Hard Disk	2 SATA
GENERAL	
Power	12V/4A
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Dimension	350mm(L)x 295mm(W)x 45mm(H)
Product Weight	1900g

Key features

- Support AHD/TVI/CVI/IP 1080P series front-end real-time encoding;
- Support VGA,CVBS, HDMI 1080P HD output;
- Support HDVI Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (Firefox, IE) ;
- Support more than languages, no nation boundaries;
- Perfect protection circuit, unique triple watchdog function
- Supporting web, IMS, provide SDK development

Interface:



Dimension:

