

SN-NVR10/04E3/016NSE


16CH 4HDD NVR



Key features

- Up to 16ch 1080P IP cameras access
- Easy to use Same Interface of GUI/WEB/Client
- 4 SATA hard disk up to 6TB
- 2RJ45 10M/100M/1000M network interface
- Simultaneous HDMI&VGA up to 1080P output
- 3 USB Host
- 2ch Alarm I/O
- 1ch Audio I/O
- 1.5U

Dimension



Interface Introduction

1. RJ45 10M/100M/1000M Network interface
2. Reset
3. Audio I/O
4. VGA output
5. HDMI output
6. USB3.0 Port
7. Alarm I/O
8. AC Power Supply

Specifications

VIDEO/AUDIO INPUT	
Video Input	16ch
Incoming Bandwidth	160Mbps ,(main stream 128Mbps ,sub stream 32Mbps)
Outgoing Bandwidth	Total 128Mbps
Audio Input	G711_A/G711_U
VIDEO/AUDIO OUTPUT	
Live View/Playback/Recording Resolution	6MP/5MP/4MP/3MP/1080P/960P/720P/D1/VGA/CIF/QCIF
Frame Rate	6MP/5MP/4MP/3MP@15fps; 1080P@30fps;
Live View/Playback Resolution	Live View: 16ch D1/4ch 1080P/1ch 6MP ,@30fps Playback: 4ch 1080P/1ch 6MP
HDMI/VGA Output	1920x1080/60Hz,1280x720/60Hz,1024x768/60Hz
Audio Output	1ch,Line out
HARD DISK	
SATA HDD	4SATA interface for 4HDD
Mounting Mode	Embedded
Capacity	Up to 6TB for each disk
NETWORK	
Network Interface	2 RJ45 10M/100M /1000M network interface
Protocol	RTP/RTCP,TCP/UDP,HTTP,DHCP,DNS,NTP
POE Interface	N/A
POE Max Power	N/A
INTERFACE	
HDMI/VGA	1ch HDMI, 1ch VGA
USB	USB 2.0 x2, USB 3.0 x1
Audio I/O	1ch MIC in,1ch audio line out
Alarm I/O	2ch Alarm output, 2ch Alarm input
Reset Button	Yes
GENERAL	
Power Supply	AC110/220V,47-63Hz ,Max input 200W
Power Consumption	Max 15W(without HDD,USB)
Operating Temperature	-10°C ~ 45°C (14°F ~ 113°F)
Operating Humidity	0% - 90% RH
Chassis	1.5U
Product Dimensions	440x376x67mm
Product Weight	3.6kg