

# SN-NVR10/08E3/032NSH


# 32CH 8HDD H.265/H.264 NVR



### Key features

- Up to 32ch IP cameras access
- Easy to use Same Interface of GUI/WEB/Client
- 8 SATA hard disk each up to 8TB
- 2RJ45 10M/100M/1000M network interface
- Simultaneous HDMI&VGA ,up to 4Koutput
- 2 x 2.0&1x3.0 USB Host
- 1ch Audio I/O
- 16ch Alarm input, 4ch Alarm output

### Dimension



### Interface Introduction

1. Alarm I/O and RS485
2. Reset
3. Audio I/O
4. RJ 45 10M/100M/1000M Network interface
5. RJ 45 10M/100M/1000M Network interface
6. HDMI1 output
7. VGA output
8. HDMI2 4K output
9. RS232 output
10. USB output
11. eSATA output
12. Power ON/OFF switch
13. AC110/220V power supply

### Specifications

VIDEO/AUDIO INPUT	
Video Input	32ch h.265/h.264 8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/etc.
Incoming Bandwidth	256Mbps ,(main stream 192Mbps ,sub stream 64Mbps)
Outgoing Bandwidth	Total 256Mbps, Remote Live-view & Playback
Audio Input	1ch,Line in
VIDEO/AUDIO OUTPUT	
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/D1/VGA/CIF/QCIF
Frame Rate	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P@25fps(PAL)
Live View/Playback Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/D1/VGA/CIF/QCIF
Live View/Playback Capacity	Live View 32ch 720p/16ch 1080p/8ch 4MP/4ch 8MP, Playback 4ch 8MP/6MP/5MP/4MP/3MP/1080P/720P
HDMI/VGA Output	HDMI1:1920x1080/60Hz,1280x720/60Hz,1024x768/60Hz HDMI2: 3840x2160/60Hz,1920x1080/60Hz,1280x720/60Hz,1024x768/60Hz z,VGA :1920x1080/60Hz,1280x720/60Hz,1024x768/60Hz
Audio Output	1ch,Line out
HARD DISK	
SATA HDD	8 HDD Slot; Up to 8TB for each disk
Mounting Mode	Embedded
Capacity	Up to 8TB for each disk (Max 64TB)
NETWORK	
Network Interface	2 RJ45 10M/100M/1000M
Protocol	RTP/RTCP,IPv4,IPv6,TCP/UDP,SMTP,HTTP,DHCP,DNS,NTP
POE Interface	N/A
System Compatibility	SDK
INTERFACE	
HDMI/VGA	2ch HDMI, 1ch VGA
USB	USB 2.0 x2,USB 3.0 x1
Audio I/O	1ch MIC in,1ch audio line out
Alarm I/O	16ch Alarm input, 4ch Alarm output
Reset Button	Yes
GENERAL	
Power Supply	AC110/220V, 47-63Hz, Max input 200W
Operating Temperature	-10℃ ~+55℃
Operating Humidity	0% - 90% RH
Chassis	2U
Product Dimensions	440x435x99.8mm
Product Weight	7.2kg