

TC-NR1032M7-S8

32CH 8HDD NVR


Tiandy



Key Features

- 32-ch 6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input
- 1-ch 6MP/5MP/4MP/4-ch 3MP/8-ch 1080P/16-ch 720P/32-ch 4CIF Realtime Display
- 4-ch 3MP/8-ch 1080P/16-ch 720P/4CIF Sync Playback
- Up to 6MP Resolution Recording
- 2xHDMI, Different Video Source
- HDD Quota and Group Management
- Dual Gigabit Network Interfaces
- Built-in 2-ch Video Analytics(VCA)
- Support 32-ch Intelligent Analysis Process
- Smart Search&Recording, Plug&Play
- Support ANR Function
- Support N+1 Hot Standby Function
- 8 SATA(Up to 32TB), Alarm I/O 16/4, Audio I/O 1/2, 3 USB
- CE, FCC, RoHS

Dimensions



Video/Audio Input	
IP video input	32-ch
Two-way Audio Input	1-ch, BNC(2.0 Vp-p, 1kΩ)
Network	
Incoming Bandwidth	200Mbps
Outgoing Bandwidth	120Mbps
Remote Connection	16 Users, Up to 48ch Videos
Browser	IE8,IE9,IE10,IE11,Chrome30,Firefox24
Mobile Software	P2P&DDNS for IOS&Android (Tiandy: TD Viewer, Neutral: Smartwatchman)
Internet Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/DHCP/PPPoE/DDNS/NFS/FTP/NTP/HTTPS/RTSP/SMTP/HTTPS/SNMP
Email	Activated by Alarm
ANR	Y, Auto download video from camera SD card, Which was stored when disconnection (Only Support Tiandy ANR IP Camera)
Advanced	Remaining Bandwidth Display
Video/Audio Output	
CVBS Output	1-ch, BNC(1.0Vp-p, 75Ω) Resolution 704x576(PAL); 704x480(NTSC)
HDMI Output	2-ch Resolution:1920x1080,1280x720,800x600,1024x768,1366x768,1440x900,1280x800
VGA Output	1-ch Resolution: 1920x1080,1280x720,800x600,1024x768,1366x768,1440x900,1280x800 Adjustable Output mode, Self-adaptive Resolution
Frame Rate	Mainstream 25fps(P)/30fps(N) Substream 25fps(P)/30fps(N)
I-Frame Record	Y
Recording Resolution	6MP(2752*2208,3008*2008,2408*2008)/5MP(2448*2048,2560*1920,2592*1944,2592*1920,2528*2128)/4MP(2560*1440,2592*1520)/Q5XGA(2560*2045)/3MP(2048*1536)/1080P/U XGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Audio Output	2-ch, BNC(Linear Electrical Level, 600Ω)
Synchronous Playback	4-ch 3MP/8-ch 1080P/16-ch 720P/4CIF
Decoding	
Live View/Playback	6MP(2752*2208,3008*2008,2408*2008)/5MP(2448*2048,2560*1920,2592*1944,2592*1920,2528*2128)/4MP(2560*1440,2592*1520)/Q5XGA(2560*2045)/3MP(2048*1536)/1080P/U XGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Capability	1-ch 6MP/5MP/4MP/4-ch 3MP/8-ch 1080P/16-ch 720P/32-ch 4CIF
Display Split	1/4/6/8/9/13/16/25/36
E-Zoom	Y
Hard Disk	
SATA	8 SATA for 8 HDDs
eSATA	Y, Only for Backup
Capacity	Up to 6TB Capacity for Each HDD
NTFS Files System	Y
HDD Management	Group and Quota
External Interface	
Network Interface	2 RJ-45 10/100/1000Mbps Self-adaptive Ethernet Interfaces
Serial Interface	2 RS-485, Keyboard
USB Interface	2 x USB2.0, 1x USB3.0
Alarm In	16-ch
Alarm Out	4-ch
Advance	
NAS	NFS Protocol, Support Manual Backup Only
Plug and Play	Y, Only for Tiandy Cameras
Corridor Mode	Y, 16:9 to 9:16, Only for Tiandy Cameras
Video Analytics(VCA)	2-ch Built-in/ 32-ch Tiandy Camera VCA Process (Tripwire and Perimeter)
Smart Search	Quickly Search Target VCA Videos , Only for Tiandy Cameras
Trigger Recording	Manual/Timing/Motion Detection/Port Alarm/VCA/Video Occulsion
Smart Recording	Set Different Recording Bite Rate for Different Time
Alarm Recording	Pre Alarm Default 10s (5/10/15/60s Optional) , Post Alarm Default 10s (10/15/30/60/600s Optional) .
Onvif	Onvif(Profile S)
General	
Language	English, Spanish, Korean, Italian,Turkish,Thai, Russian, Traditional Chinese, French, Polish
Power Supply	100 ~ 240V AC, 6.3A, 50 ~ 60Hz
Consumption(without HDD)	≤ 44 W
Working Temperature	-10 °C ~ +55 °C (+14 °F~ + 131 °F)
Working Humidity	10 % ~ 90 %
Chassis	19-inch Rack-mounted 2U Chassis
Dimensions	89mmx440mmx472mm
Weight	7.2KG (without HDD), 9.8KG (with Packing Box)

* The latest product information / specification can be found at <http://en.tiandy.com/>



Tiandy Digital Technology Co., Ltd. | en.tiandy.com

Add: No.8, Huake Rd2, Binhai Hi-Tech Industry(Huayuan), Tianjin 300384 China

Tel: +86-22-58596037 Email: sales@tiandy.com

