

Network Video Recorder

NVR201LP Series



Key Features

4/8-channel input

Third-party IP cameras supported with ONVIF conformance

HDMI and VGA output up to 1080P

Up to 4 Megapixels resolution recording

Accurate retrieval, instant playback

1 SATA HDD up to 8 TB

Plug & Play with up to 4/8 independent PoE network interfaces

Support for P2P, UPnP, NTP, DHCP, PPPoE


Support for mobile client access

Specifications

Model	NVR201-04LP	NVR201-08LP
Video/Audio Input		
IP Video Input	4-ch	8-ch
Two-way Audio Input	1-ch,RCA	
Network		
Incoming Bandwidth	40Mbps	80Mbps
Outgoing Bandwidth	64Mbps	
Remote Users	128	
Video/Audio Output		
HDMI/VGA Output	HDMI/VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
Recording Resolution	4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	
Audio Output	1-ch,RCA	
Synchronous Playback	4-ch	8-ch
Decoding		
Compression	H.264	
Live view/Playback	4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	
Capability	2 x 4MP@20, 4 x 1080P@30	4 x 4MP@20, 8 x 720p@25
Hard Disk		
SATA	1 SATA interface	
Capacity	up to 8TB for each disk	
External Interface		
Network Interface	1 RJ-45 10M/100M Self-adaptive Ethernet Interface	
USB Interface	Rear panel: 1 x USB2.0, 1 x USB3.0	
PoE		
Interface	4 independent 100 Mbps PoEnetwork interfaces	8 independent 100 Mbps PoEnetwork interfaces
Supported Standard	IEEE 802.3at	
General		
Power Supply	48 V DC	48~52V DC
Consumption (without HDD)	≤8 W	
Working Temperature	-10°C ~ + 55°C (+14°F ~ +131°F)	
Working Humidity	10% ~ 90%	
Dimensions	205 × 205 × 42mm (8.1" × 8.1" × 1.7")	270 × 205 × 42 mm (10.6" × 8.1" × 1.7")
Weight (without HDD)	≤ 0.58 Kg (1.27lb)	≤ 0.72 Kg (1.59 lb)


Dimensions

Take NVR201-08LP for example



Rear Panel

Take NVR201-08LP for example



Zhejiang Uniview Technologies Co.,Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2011-2017 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.