



FD8182-T



FD8182-F2

Fixed Dome Network Camera



5MP · 30M IR · WDR Enhanced · P-iris · Remote Focus ·
3DNR · Smart Stream · Smart IR · Video Rotation · PIR · Defog

VIVOTEK's FD8182 is a series of economic professional indoor fixed dome network cameras in VIVOTEK's 5MP Lite series. Designed to provide higher resolution and sharper image with more details, the FD8182 series offer up to 15 fps at 5-Megapixel or 30 fps at 1080p resolution. With powerful 3D Noise Reduction technology and Smart Stream technology the FD8182 series can also optimize resolution for a desired object or area to maximize efficiency of bandwidth usage.


Increasing its flexibility, VIVOTEK's FD8182 series provides options for both fixed focus used for simple operation without additional power, and remote focus with built-in stepping motors and P-iris to provide precise adjustment remotely.

To meet the demands of indoor applications, VIVOTEK's FD8182 series is also equipped with a PIR sensor to help detect unexpected events and provide the the appropriate response in real time.


With the highly flexible VADP (VIVOTEK Application Development Platform), users can extend the features of this series by adding third-party applications for the FD8182-F2 and the FD8182-T. Thus, the FD8182 series is not only equipped with multiple focusing methods, but is also highly flexible and able to be expanded to meet the requirements of a wide variety of indoor applications.

Key Features

- 5-Megapixel CMOS Sensor
- 15 fps @ 2560x1920
- 3 ~ 9 mm, Remote Focus, P-iris Lens (FD8182-T)
- Built-in IR Illuminators, Effective up to 30 Meters
- WDR Enhanced for Unparalleled Visibility in Bright and Dark Environments
- Smart Stream to Optimize Bandwidth Efficiency
- 3D Noise Reduction
- Two-way Audio
- PIR
- Video Rotation for Corridor View
- Support Installation with AM-712 Indoor Conduit Box
- VIVOTEK VCA (Video Content Analysis) Support



Smart Stream - Manual Mode




Smart Stream - Auto Mode



Store



Train Station



Hotel



Airport

Technical Specifications

Model	FD8182-T: Vari-focal, P-iris, Remote Focus FD8182-F2: Fixed-focal	Interface	10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
System Information		ONVIF	Supported, specification available at www.onvif.org
CPU	Multimedia SoC (System-on-Chip)	Intelligent Video	
Flash	1Gb	Video Motion Detection	Five-window video motion detection
RAM	4Gb	VCA	Line crossing detection, field detection, loitering detection *Available per project request.
Camera Features		Alarm and Event	
Image Sensor	1/3.2" Progressive CMOS	Alarm Triggers	Motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection, audio detection
Maximum Resolution	2560x1920 (SMP)	Alarm Events	Event notification using digital output, HTTP, SMTP, FTP and NAS server, SD Card File upload via HTTP, SMTP, FTP, NAS server and SD card
Lens Type	FD8182-T: Vari-focal FD8182-F2: Fixed-focal	General	
Focal Length	FD8182-T: f = 3 ~ 9 mm FD8182-F2: f = 2.8 mm	Smart Focus System	FD8182-T: Remote Focus
Aperture	FD8182-T: F1.2 ~ F2.3 FD8182-F2: F1.8	Connectors	RJ-45 cable connector for Network/PoE connection Audio input Audio output DC 12V power input Digital input*1 Digital output*1
Auto-iris	P-iris (FD8182-T)	LED Indicator	System power and status indicator
Field of View	FD8182-T: 35° ~ 78° (Horizontal) 27° ~ 54° (Vertical) 44° ~ 101° (Diagonal) FD8182-F2: 90° (Horizontal) 67° (Vertical) 118° (Diagonal)	Power Input	DC 12V IEEE 802.3af/at PoE Class 0
Shutter Time	1/5 sec. to 1/32,000 sec.	Power Consumption	FD8182-T: Max. 9.5 W FD8182-F2: Max. 9 W
WDR Technology	WDR Enhanced	Dimensions	Ø 138 x 103 mm
Day/Night	Removable IR-cut filter for day & night function	Weight	541 g
Minimum Illumination	FD8182-T: 0.04 Lux @ F1.2 (Color) 0.001 Lux @ F1.2 (B/W) FD8182-F2: 0.39 Lux @ F1.8 (Color) 0.001 Lux @ F1.8 (B/W)	Safety Certifications	FD8182-T: CE, LVD, FCC Class B, VCCI, C-Tick, UL FD8182-F2: CE, LVD, FCC Class B, VCCI, C-Tick
Pan/tilt/zoom Functionalities	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built in)	Operating Temperature	Starting Temperature: 0°C ~ 50°C (32°F~ 122°F) Working Temperature: -10°C ~ 50°C (14°F~ 122°F)
IR Illuminators	Built-in IR illuminators, effective up to 30 meters with Smart IR IR LED*8	Warranty	36 months (FD8182-T) 24 months (FD8182-F2)
On-board Storage	Slot type: Micro SD/SDHC/SDXC card slot Seamless Recording	System Requirements	
Video		Operating System	Microsoft Windows 7/8/Vista/XP/2000
Compression	H.264 & MJPEG	Web Browser	Mozilla Firefox 7~43 (streaming only) Internet Explorer 7/8/9/10/11
Maximum Frame Rate	15 fps @ 2560x1920 15 fps @ 2048x1536 30 fps @ 1920x1080 In both compression modes	Other Players	VLC: 1.1.11 or above Quicktime: 7 or above
Maximum Streams	4 simultaneous streams	Included Accessories	
S/N Ratio	67 dB	CD	User's manual, quick installation guide, Installation Wizard 2
Dynamic Range	70 dB	Others	Quick installation guide, warranty card, alignment sticker/desiccant bag, screw pack
Video Streaming	Adjustable resolution, quality and bitrate; Smart Stream	Dimensions	
Image Settings	Adjustable image size, quality and bit rate, Time stamp, text overlay, flip & mirror, Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks, Scheduled profile settings, 3D noise reduction, video rotation, defog		
Audio			
Audio Capability	Two-way Audio (full duplex)		
Compression	G.711, G.726		
Interface	Built-in microphone External line input External line output		
Network			
Users	Live viewing for up to 10 clients		
Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, SSL, TLS		

Compatible Accessories

Mounting Kits



AM-215 (v02)
L Shape Bracket



AM-514 (v01)
Adapter Ring



AM-527 (v01)
Mounting Adapter



AM-712
Conduit Box



AP-FXC-0201
PoE Extender with
Conduit Box

PoE Kits