

Technical Specifications

System <ul style="list-style-type: none">CPU: Multimedia SoCFlash: 128MBRAM: 256MBEmbedded OS: Linux 2.6	Networking <ul style="list-style-type: none">10/100 Mbps Ethernet, RJ-45Onvif supportProtocols: IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP and 802.1x
Lens <ul style="list-style-type: none">IP8151: CS-mount, vari-focal, f = 3.1~8 mm, F1.2, auto irisIP8151P: CS-mount, vari-focal, f = 3.1~8 mm, F1.2, P-irisRemovable IR-cut filter for day & night function	Alarm and Event Management <ul style="list-style-type: none">Triple-window video motion detectionTamper detectionOne D/I and one D/O for external sensor and alarmEvent notification using HTTP, SMTP or FTPLocal recording of MP4 file
Field of View <ul style="list-style-type: none">35.2~86.7° (horizontal)26.5~64.4° (vertical)43.9~110.3° (diagonal)	On-board Storage <ul style="list-style-type: none">SD/SDHC card slotStores snapshots and video clips <small>*Note: No SD/SDHC card slot & local storage function for Argentina.</small>
Shutter Time <ul style="list-style-type: none">1/5 sec. to 1/40,000 sec.	Security <ul style="list-style-type: none">Multi-level user access with password protectionIP address filteringHTTPS encrypted data transmission802.1X port-based authentication for network protection
Image Sensor <ul style="list-style-type: none">1/3" CMOS sensor in 1280x1024 resolution	Users <ul style="list-style-type: none">Live viewing for up to 10 clients
Minimum Illumination <ul style="list-style-type: none">0.04 Lux / F1.2 (Color)0.001 Lux / F1.2 (B/W)	Dimension <ul style="list-style-type: none">154 mm (D) x 72 mm (W) x 62 mm (H)
Video <ul style="list-style-type: none">Compression: H.264, MJPEG & MPEG-4Streaming:<ul style="list-style-type: none">Multiple simultaneous streamsH.264 streaming over UDP, TCP, HTTP or HTTPSMPEG-4 streaming over UDP, TCP, HTTP or HTTPSMPEG-4 multicast streamingMJPEG streaming over HTTP or HTTPSSupports activity adaptive streaming for dynamic frame rate controlSupports ePTZ for data efficiencySupports 3GPP mobile surveillanceFrame rates:<ul style="list-style-type: none">H.264: Up to 30 fps at 1280x1024MPEG-4: Up to 30 fps at 1280x1024MJPEG: Up to 30 fps at 1280x1024Interface:<ul style="list-style-type: none">BNC connector for video outputNTSC/PAL video output switchFocus assist button (IP8151P only)	Weight <ul style="list-style-type: none">IP8151 Net: 670 g (Without lens)IP8151P Net: 675 g (Without lens)
Image Settings <ul style="list-style-type: none">Adjustable image size, quality and bit rateTime stamp and text caption overlayFlip & mirrorConfigurable brightness, contrast, saturation, sharpness, white balance and exposureAGC, AWB, AESWDR enhancedAutomatic, manual or scheduled day/night modeBLC (Backlight Compensation)Supports privacy masks	LED Indicator <ul style="list-style-type: none">System power and status indicatorSystem activity and network link indicator
Audio <ul style="list-style-type: none">Compression:<ul style="list-style-type: none">GSM-AMR speech encoding, bit rate: 4.75 kbps to 12.2 kbpsMPEG-4 AAC audio encoding, bit rate: 16 kbps to 128 kbpsG.711 audio encoding, bit rate: 64 kbps, µ-Law or A-Law mode selectableInterface:<ul style="list-style-type: none">Built-in microphoneExternal microphone inputAudio outputExternal/Internal microphone switchSupports two-way audioSupports audio mute	Power <ul style="list-style-type: none">12V DC24V ACPower consumption: Max. 3.6 W802.3af compliant Power-over-Ethernet (Class 2)
	Approvals <ul style="list-style-type: none">CE, LVD, FCC, VCCI, C-Tick, UL
	Operating Environments <ul style="list-style-type: none">Temperature: -10 ~ 50 °C (14 ~ 122 °F)Humidity: 90% RH
	Viewing System Requirements <ul style="list-style-type: none">OS: Microsoft Windows 7/Vista/XP/2000Browser: Mozilla Firefox, Internet Explorer 6.x or aboveCell phone: 3GPP playerReal Player: 10.5 or aboveQuick Time: 6.5 or above
	Installation, Management, and Maintenance <ul style="list-style-type: none">RS-485 interface for scanners, pan/tiltsInstallation Wizard 232-CH ST7501 recording softwareSupports firmware upgrade
	Applications <ul style="list-style-type: none">SDK available for application development and system integration
	Warranty <ul style="list-style-type: none">36 months

All specifications are subject to change without notice. Copyright © 2011 VIVOTEK INC. All rights reserved. P/N: 971003801

SUPREME
A NEW DEFINITION OF HD



Fixed Network Camera
IP8151/51P

Supreme Night Visibility • Full Frame Rate • WDR Enhanced



VIVOTEK IP8151/51P represent the next-generation in video quality in network cameras. As part of VIVOTEK's SUPREME Series, the cameras feature the utmost in picture clarity through utilization of SONY's latest sensor technology, dubbed "Exmor™", which enables the camera to capture exceptional details during daytime, as well as to offer unparalleled visibility under low-light conditions through its Supreme Night Visibility feature. Additional value-added functions that give users more flexibility and efficiency of use include WDR Enhancement, which allows users to identify image details in extremely bright and dark environments.

The IP8151P model features a number of additional premium features, giving users more flexibility and efficiency of use. The advanced P-Iris lens controls the iris using the built-in stepping motor with extreme precision via software control to maintain the iris opening at an optimal level at all times, resulting in superior sharpness, depth of field, and image quality. The IP8151P is also equipped with a Focus Assist button, assisting the user to optimally adjust the camera focus. When pressing the Focus Assist button on the camera unit, an indicator display will be shown on the screen with detailed focusing information. Keeping the button pressed will enable zooming in on the target area for fine tuning, resulting in better usability as well as picture clarity.

Both the IP8151 and IP8151P also feature a myriad of other high-end features such as SD/SDHC card slot*, PoE, and multiple streams, making it the ideal choice for the most demanding monitoring applications. By providing the best quality sharp, smooth video, plus exceptional performance in low-light conditions, the IP8151/51P can secure a variety of sites such as retail stores, school campuses, and much more.

* No SD/SDHC card slot & local storage function for Argentina. * Exmor is a trademark of Sony.



VIVOTEK INC.
6F, No.192, Lien-Cheng Rd., Chung-Ho, New Taipei City, 235, Taiwan, R.O.C.
| T: +886-2-82455282 | F: +886-2-82455532 | E: sales@vivotek.com

VIVOTEK USA, INC.
2050 Ringwood Avenue, San Jose, CA 95131
| T: 408-773-8686 | F: 408-773-8298 | E: salesusa@vivotek.com

