

IP Video Specialty Cameras

►DINION IP capture 5000



►DINION IP imager 9000 HD



►FLEXIDOME IP corner 9000 MP



■ Available – Not available

Commercial Type Number		NER-L2Rx-1	NAI-90022-AAA	NCN-90022-F1
Bosch USPs	intelligent Dynamic Noise Reduction (iDNR)	-	■	■
	intelligent Auto Exposure (iAE) / iDefog	-/-	■/-	-/-
	starlight (extreme low-light sensitivity)	-	-	-
	4K ultra HD	-	-	-
	Built-in Intelligent Video Analysis (IVA)	-	■	-
Basic features	Maximum resolution	576p	HD 1080p	1080p
	Image sensor type	1/3"	1/2.7"	1/2.7"
	Max. frames per second (fps)	30 fps@576p	30 fps@1080p	30 fps@1080p
	Indoor / outdoor / in-vehicle	-/■/-	-/■/-	■/-/-
	Day/night	■	■	■
	Wide Dynamic Range (WDR)	120dB	76dB (with IAE +16dB)	76dB
	ONVIF conformant	■	■	■
	Built-in microphone	-	-	-
	Power over Ethernet (PoE)	■	■ (HiPoE)	■
Advanced features	Compression (H.264 & MJPEG) / multi-streaming	■/4 streams	■/4 streams	■/4 streams
	Privacy masking	-	■	■
	Region Of Interest tracking	-	■	-
Alarm triggering	Tamper detection	■	■	■
	Video motion detection	■	■	■
	Intelligent Video Analysis (IVA)	-	■	-
	Audio detection	-	■	■
Sensitivity	Minimum illumination day mode (color)	0 lux	0.4 lux	0.3 lux
	Minimum illumination night mode (black / white)	0 lux	0 lux	0 lux
	Night vision	■	■ (infrared)	■ (infrared)
	Max. range at night	28 m (92 ft)	120 m (394 ft)	9 m (30 ft)
Lens	Automatic Back Focus (ABF)	-	■	-
	Automatic varifocal	-	■	-
	Focal length	5 - 50 mm varifocal (calibrated to optimal capture distance)	10 - 23 mm	2 mm
	Horizontal Angle of View (HAoV)	5.3°-31.9°	14.8°-34°	121°
DCRI distances	Detection / Classification / Recognition / Identification (Distances in m with 100 lux illumination)	-	150-352/77-181/52-122/21-49	20/10/7/3
Storage	Memory card slot	■ Up to 2 TB	■ Up to 2 TB	■ Up to 2 TB
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input / output	-/-	1/1	1/1
	Audio in/out	-/-	■/■	■/■
	Hybrid* / confrontation monitor	-/-	■/■	-/-
Housing	Weather rating	IP67	IP66	IP65
	Vandal resistant	-	IK10	IK10
	Operating temperature	-40° to 50° C (-40° to 122° F)	-40° to 50° C (-40° to 122° F)	-10° to 50° C (14° to 122° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system