

Compact Color Camera VBC-255 Series

www.boschsecurity.com



BOSCH

Invented for life



Advantage Line

The VBC-255 is a compact, rugged, 1/3-inch image format digital color CCD camera. The superior sensitivity, 540 TVL resolution and picture quality provide optimal performance in virtually all situations. The lens wizard automatically detects the lens and allows the installer to easily adjust the lens level and focus without special tools or filters. Automatic black level enhances contrast by removing veiling glare from the picture. NightSense is used to further extend the excellent sensitivity by a factor of 3 in monochrome operation. This fully automatic camera is ready to operate, and is easy to install.

Features

- ▶ Superior picture quality
- ▶ Outstanding resolution (540 TVL)
- ▶ Extended sensitivity with NightSense
- ▶ Auto detection of lens
- ▶ Easy to install

2 | Compact Color Camera VBC-255 Series

Technical specifications

Electrical			
Model No.	Rated Voltage		Range
VBC-255-11 (C)	12 VDC	10.8-39 VDC	
	24 VAC 50 Hz	12-28 VAC 45-65 Hz	
VBC-255-51 (C)	230 VAC 50 Hz	85-265 VAC 45-65 Hz	
Power Consumption	4 W, excluding lens		
Imager	Interline transfer CCD, 1/3-inch image format		
Active Pixels	752 H x 582 V		
Horizontal Resolution	540 TVL		
Signal-to-Noise Ratio	50 dB		
Gain	21 dB, (max)		
Electronic Shutter	Automatic, 1/50 to 1/125000 sec.		
Aperture Correction	Horizontal and vertical, symmetrical		
Backlight Compensation	Center window weighting		
White Balance	Automatic sensing (2500–9000 K)		
Remote Control	Bilinx coaxial communication		
Video Output	Composite video 1.0 Vpp, 75 Ohm		
Line-Lock synchronization (AC only)	Synchronizes the camera to the power line zero crossing for roll-free vertical interval switching. Vertical phase delay can be adjusted (0-358 degrees) to allow vertical synchronization in multi-phase power installations.		
Free running synchronization (DC-supply or L/L off)	Internal crystal reference is standard on all models.		
Sensitivity			
(3200 k)			
	Usable Picture (30 IRE)	Usable Picture (50 IRE)	Full Video
Scene Illumination ¹⁾ (color mode)	0.30 lux (0.03 fc)	0.65 lux (0.07 fc)	2.6 lux (0.26 fc)
Imager Illumination (color mode)	0.045 lux (0.005 fc)	0.10 lux (0.010 fc)	0.40 lux (0.040 fc)
Scene Illumination ¹⁾ (night mode)	0.12 lux (0.012 fc)	0.26 lux (0.026 fc)	1.04 lux (0.104 fc)
Imager Illumination (night mode)	0.018 lux (0.002 fc)	0.040 lux (0.004 fc)	0.16 lux (0.016 fc)
Mechanical			
Dimensions (H x W x D)	58 x 66 x 122 mm (2.28 x 2.6 x 4.8 in.) including connectors		
Weight	0.45 kg (0.99 lb)		
Connectors	Video Output: BNC Video/DC-iris connector: 4-pin EIA-J		
Camera Mounting	Top and Bottom, 1/4-inch 20 UNC		
Lens Mounting	C and CS		
Environmental			
Operating Temperature	-20°C to 50°C (-4°F to 122°F)		
Storage Temperature	-25°C to 70°C (-13°F to 158°F)		
Operating Humidity	5% to 93% non-condensing		
Power			

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com

Power connector (VBC-255-11, VBC-255-11C)	Push type connectors, polarity independent, isolated from video output terminals
Power connector (VBC-255-51)	2-wire power cord with Euro plug
Power connector (VBC-255-51C)	2-wire power cord with Chinese plug



Notice

Lens is not included

Certifications and approvals	
Region	Certification
Europe	CE
Standards	
	FCC Part 15, Class B
	EN55022: Class B
	EN50130-4
	EN60065
Ordering information	
VBC-255-11 Compact Color Camera, 12 VDC/24 VAC	VBC-255-11
VBC-255-11C Compact Color Camera, 12 VDC/24 VAC, China	VBC-255-11C
VBC-255-51 Compact Color Camera, 230 VAC	VBC-255-51
VBC-255-51C Compact Color Camera, 230 VAC, China	VBC-255-51C