

Product Highlights

Compact Size and Easy Deployment

Ultra small size and PoE allows for easy deployment in hard-to-reach places or areas where discrete surveillance is needed

HD Video Quality and Detail

High resolution 1 megapixel sensor provides 1280 x 800 resolution, built-in infrared LEDs allow nighttime viewing up to 15 feet

mydlink-enabled Cloud Access

Easy remote viewing and management of your camera on your mobile device or through the mydlink website



Includes white & black case options

DCS-6004L

HD Mini Dome Network Camera

Features

Camera

- 1/4" 1 megapixel CMOS progressive sensor
- 10x Digital zoom and 15 feet IR illumination
- Built-in microphone and audio out for 2-way communication
- ONVIF compliant

Connections

- 10/100 Power over Ethernet port
- microSD/SDHC card slot for onboard storage²

Image & Video

- HD resolution (1280 x 800 max)
- H.264, MPEG-4 and Motion JPEG compression
- Simultaneous multi-stream support
- Supports multiple access lists
- Built-in Samba client for saving to a server

Flexibility and Convenience

- Powered by PoE or included power adapter
- Includes white and black case options
- Video can be viewed with web browser, video management software or mydlink cloud portal and mobile app

Built for Versatility

The DCS-6004L comes with a wealth of features that enhance its surveillance capabilities, making it ideal for any situation. The ultra small form factor allows you to mount the camera in areas that need to be monitored without the camera being an eyesore. The DCS-6004L is perfect for deployment into areas that lack power with its PoE feature. A built-in microphone and audio out port allow for 2-way communication during an event.

Peace Of Mind With 24/7 Monitoring of Any Environment

The DCS-6004L is a standalone surveillance camera that requires no special hardware or software, and can run independently even without a PC. Send e-mail notifications with snapshots or video clips whenever motion or sound is detected using just the DCS-6004L and an Internet connection. You can customize areas of the video to monitor for motion to keep watch over entryways, and you can set volume limits to detect when a loud sound is picked up by the camera. Night time monitoring is possible with the built-in infrared LEDs which allow for nighttime viewing of up to 15 feet, enabling round-the-clock monitoring of a home or small office.

Instant Anywhere Access with mydlink Cloud Service


The HD Mini Dome Network Camera is mydlink-enabled, which means that you can access and configure your camera remotely, no matter where you are. With a mydlink service enabled camera, see your camera's live view through the mydlink website, or download the mydlink mobile app and view your camera directly on your smartphone or tablet. Keep an eye on your home while you're at work, or check on the office when you're out on the road; mydlink makes it all possible.

A Complete, Expandable Surveillance Solution



The DCS-6004L is a self-sufficient surveillance solution, capable of recording snapshots and video to a microSD card without requiring a PC or network storage device. If you want to expand your surveillance options, D-ViewCam

management software is also included, giving you the ability to manage up to 32 cameras with a robust set of features, including multi-camera views and automated e-mail alerts to keep you informed of suspicious or unusual activities.

Technical Specifications		
Camera		
Camera Hardware Profile	<ul style="list-style-type: none"> • 1/4" 1 megapixel progressive CMOS sensor • Minimum illumination: 0 lux (with IR LED on) • Built-in microphone and audio out port • 10x digital zoom • Fixed length: 2.8 mm • Aperture: F1.8 	<ul style="list-style-type: none"> • Angle of view: <ul style="list-style-type: none"> • (H) 75° • (V) 48° • (D) 89° • Minimum object distance: 20"
Image Features	<ul style="list-style-type: none"> • Configurable image size, quality, frame rate, and bit rate • Time stamp and text overlays • Configurable privacy masks zones 	<ul style="list-style-type: none"> • Configurable brightness, saturation, contrast, and sharpness • Configurable motion detection windows
Video Compression	<ul style="list-style-type: none"> • Simultaneous H.264/MPEG-4/MJPEG compression • H.264/MPEG-4 multicast streaming 	<ul style="list-style-type: none"> • JPEG for still images
Video Resolution	<ul style="list-style-type: none"> • 16:9 -1280 x 800, 1280 x 720, 800 x 450, 640 x 360, 480 x 270, 320 x 176 up to 30 fps recording¹ 	<ul style="list-style-type: none"> • 4:3 -1024 x 768, 800 x 600, 640 x 480, 480 x 360, 320 x 240 up to 30 fps recording¹
Audio Support	<ul style="list-style-type: none"> • G.711: 64 kbps 	<ul style="list-style-type: none"> • AAC: 64 kbps
External Device Interfaces	<ul style="list-style-type: none"> • 10/100 BASE-TX Fast Ethernet 802.3af PoE port 	<ul style="list-style-type: none"> • microSD/SDHC card slot²
Network		
Network Protocols	<ul style="list-style-type: none"> • IPv6 • IPv4 • TCP/IP • UDP • ICMP • DHCP client • NTP client (D-Link) • DNS client • DDNS client (D-Link) • SMTP client • FTP client 	<ul style="list-style-type: none"> • HTTP / HTTPS • Samba client • PPPoE • UPnP port forwarding • RTP / RTSP / RTCP • IP filtering • QoS • CoS • Multicast • IGMP • ONVIF compliant
Security	<ul style="list-style-type: none"> • Administrator and user group protection • Password authentication 	<ul style="list-style-type: none"> • HTTP and RTSP authentication
System Management		
Event Management	<ul style="list-style-type: none"> • Motion/Sound detection • Event notification and uploading of snapshots & video clips via e-mail or FTP 	<ul style="list-style-type: none"> • Supports multiple SMTP and FTP servers • Multiple event notifications • Multiple recording methods for easy backup
Remote Management	<ul style="list-style-type: none"> • Take snapshots/video clips and save to local hard drive via web browser 	<ul style="list-style-type: none"> • Configuration interface accessible via web browser

Mobile Support	<ul style="list-style-type: none"> • mydlink Lite/mydlink+ mobile app for iPhone™, iPad™, and Android™ and Windows mobile devices
D-ViewCam™ System Requirements	<ul style="list-style-type: none"> • Operating System: Microsoft Windows 8 / 7 / Vista / XP • Web browser: Internet Explorer 7 or higher • Protocol: Standard TCP/IP
D-ViewCam™ Software Functions	<ul style="list-style-type: none"> • Remote management/control of up to 32 cameras • Viewing of up to 32 cameras on one screen • Supports all management functions in web interface • Scheduled motion triggered, or manual recording options
Physical	
Weight	<ul style="list-style-type: none"> • 4.6 ounces (130 grams) without mounting plate
External Power Adapter	<ul style="list-style-type: none"> • Input: 100 to 240 V AC, 50/60 Hz • Output: 5V DC, 1.2 A
Power Consumption	<ul style="list-style-type: none"> • 3.5 Watts
Temperature	<ul style="list-style-type: none"> • Operating: 32° to 104° F (0° to 40° C) • Storage: -4° to 158° F (-20° to 70° C)
Humidity	<ul style="list-style-type: none"> • Operating: 20% to 80% non-condensing • Storage: 5% to 95% non-condensing
Certifications	<ul style="list-style-type: none"> • CE • CE LVD • FCC Class B • C-Tick
Dimensions	 <p>Technical drawings of the camera showing dimensions:</p> <ul style="list-style-type: none"> Height: 2.0" (50 mm) Total Height: 2.2" (55.5 mm) Diameter: Ø 3.5" (90 mm)

HD Mini Dome Network Camera

Warranty	
Warranty	• 1 Year Warranty
Order Information	
Part Number	Description
DCS-6004L	HD Mini Dome Network Camera
Included Accessories	
	Black Collar
	White Collar

¹ Frame rates when streaming video may vary depending on network conditions and method used.

² A microSDHC Class 6 card or above is recommended, supports card capacities up to 32GB, microSD card not included.

Updated 2014/08/29 (Hardware Revision A1)

For more information

U.S.A. | 17595 Mt. Herrmann Street | Fountain Valley, CA 92708 | 800.326.1688 | dlink.com

D-Link, the D-Link logo and the D-ViewCam™ logo are registered trademarks of D-Link Corporation or its subsidiaries. All other third-party marks mentioned herein may be trademarks of their respective owners.

© 2014 D-Link. All rights reserved.