

## DH-ESS2016X-J

### 16 HDDs Mini SAS Storage Cabinet



#### Features

- > IPSAN solutions
- > High-performance, scalability, easy for data storage
- > Support storage host such as NVR, EVS, ESS, provide 200MB/s R&W to storage host
- > Support HDDs hot-swap, non-stop service when replace the HDDs, support 4TB ultra-capacity HDD, support mixed SAS and SATA HDDs
- > Redundant fans and redundant power supply, keep 7x24-hour uninterrupted running in dahua patent chassis
- > Support standard SAS protocol
- > Software and hardware optimization aim at monitoring field, Supporting other monitoring products form a complete solution
- > Support lower expansion device cascade

#### Technical Specifications

|                        |   |
|------------------------|---|
| <b>Model</b>           | <b>DH-ESS2016X-J</b>  |
| <b>System</b>          |   |
| Main Processor         | Private storage expansion CPU   |
| Operating System       | Embedded LINUX  |
| Power Supply           | Single Power Supply   |
| Fan                    | Redundant two-ball bearing fans, MTBF>100,000 hours   |
| Motherboard            | Server class(24/7 operation)  |
| Chassis                | All self-design, Hot-dip galvanized steel sheet(1.2mm thickened) High-precise aluminum alloy slide Self-patent drawer-type HDD rack |
| <b>Data Management</b> |   |
| Hard Disk              | 16 HDDs, support SAS,SATA HDDs, support 3T,4T HDDs  |
| HDD Install            | Independent HDD holder, support hot-swap  |
| Data Interface         | miniSAS interface   |

## DH-ESS2016X-J

| General             |                                       |
|---------------------|---------------------------------------|
| Power Supply        | 100V~240V,50Hz~60Hz                   |
| Power Consumption   | <400W(include HDD),<200W(exclude HDD) |
| Working temperature | 0°C~40°C                              |
| Working Humidity    | 10%~80%(non-condensation)             |
| Storage Temperature | -20°C~70°C                            |
| Storage Humidity    | 5%~90%(non-condensation)              |
| Working Elevation   | -60m~3000m                            |
| Dimension(W×D×H)    | 133mm×448mm×472mm                     |
| Weight              | 15kg                                  |
| Mounting            | 19 feet standard rack-mounted         |

---

### Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

\*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.