

DH-IPC-HDBW5241R-ASE

2MP WDR IR Dome AI Network Camera



Dahua AI series products adopt the most advanced AI technologies, including deep learning algorithms that primarily target people and vehicles, which provides higher flexibility and accuracy for end-users. This enables the Dahua AI series to offer various advanced applications such as Face Recognition, ANPR, Metadata, People Counting, traffic data statistics, etc. The complete lineup of Dahua AI includes network (PTZ) cameras, network video recorders, servers, and platform management products. Beyond seeing the world, the power of AI allows devices to perceive the environment and understand the world in a better way.

System Overview

Pro AI series contains Face Capture, Perimeter Protection and People Counting functions. Powered by deep-learning Artificial Intelligence algorithms, significantly improved accuracy. Meanwhile, the series features starlight and smart IR technology. This series fully protected from dust and water, certified to IP67 and vandal resistant to IK10 standard.

Functions

Face Capture

Face capture is a software application that automatically captures faces from within a digital image or a video frame from a video source. Dahua cameras use advanced deep learning algorithms and are trained by a large number of face data sources, enabling the camera to locate faces quickly and accurately from the video source and capture facial images.

Face Attributes

Through the use of deep learning algorithms to analyze facial images, Dahua cameras can extract six facial attributes from each frame, including Age, Gender, Expression (Jolly/Surprise/Normal/Rage/Sad/Disgusted/Confused/Frightened), Glasses, Mouth Mask, Moustache & Beard. Customers can acquire data of interest via face attributes statistics.

Perimeter Protection

Dahua's Perimeter Protection functions significantly improved accuracy. Perimeter Protection reduces false alarms and decreases pixel count requirements for object detection. Perimeter Protection features custom tripwires based on object type for automation in limited access areas such as pedestrian or vehicle-only zones. This combination of advanced AI analytics and real-time alerts to a desktop or to a mobile

- 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS
- H.265&H.264 triple-stream encoding
- 25/30fps@1080P(1920×1080)
- WDR(120dB), Day/Night(ICR), 3D DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.8mm fixed lens (3.6mm/6mm optional)
- 1/1 Alarm in/out, 1/1 audio in/out
- Max. IR LEDs Length 40m
- Micro SD memory, IP67, IK10



client reduces system requirements and resources resulting in greater surveillance system efficiency.

People Counting

People Counting function uses advanced image processing technology to capture depth information from within images. The camera pairs this information with deep learning algorithms to analyze and detect human bodies and track target objects in real time. The camera provides statistics for separate individuals' entrance and exit with up to 95% counting accuracy.

Metadata

Metadata is feature attribute information extracted from a target object which can be used for data retrieval. Dahua face detection camera can extract six facial attributes and output the metadata for analysis.

ePoE technology

The ePoE technology of Dahua, designed internally, adopts advanced 2D-PAM3 coding modulation from physical layer, and realizes full duplex transmission over 800 meters at the speed of 10Mbps, or 300 meters at the speed of 100Mbps via Cat 5 or coaxial cable media. Besides, it supports PoE and PoC power supply technology which has greatly simplified construction and wiring. Dahua ePoE technology offer a new way to accomplish long distance transmission between IP camera and network switch. It allows more flexible surveillance system design, improves reliability and saves construction and wiring cost.

Protection(IP67, IK10, wide voltage)

The camera allows for $\pm 30\%$ input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 6KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67) and impact tests (IK10), the camera is the choice for installation in even the most unforgiving environments.

Technical Specification

Camera					
Image Sensor	1/2.8" 2Megapixel progressive scan STARVIS™ CMOS				
Effective Pixels	1920(H) x 1080(V)				
RAM/ROM	512MB/128MB				
Scanning System	Progressive				
Electronic Shutter Speed	Auto/Manual, 1/3~1/100000s				
Minimum Illumination	0.002Lux/F1.6 (Color,1/3s,30IRE) 0.012Lux/F1.6 (Color,1/30s,30IRE) 0Lux/F1.6(IR on)				
IR Distance	Distance up to 40m (131ft)				
IR On/Off Control	Auto/ Manual				
IR LEDs	1				

Lens					
Lens Type	Fixed				
Mount Type	Board-in				
Focal Length	2.8mm,3.6mm,6.0mm				
Max. Aperture	F1.6				
Angle of View	H: 106°, V:57°/H: 87°, V:46°/H: 53°, V:30°				
Optical Zoom	N/A				
Aperture Type	Fixed				
Close Focus Distance	0.6m(1.97ft)/1.2m(3.94t)/2.5m(8.20ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8mm	39m(128ft)	15m(49ft)	8m(26ft)	4m(13ft)
	3.6mm	55m(180ft)	22m(72ft)	11m(36ft)	6m(20ft)
	6.0mm	83m(272ft)	33m(108ft)	17m(56ft)	8m(26ft)

Pan/Tilt/Rotation					
Pan/Tilt/Rotation Range	Pan:0°~355°; Tilt:0°~75°; Rotation:0°~355°				

Artificial Intelligence					
Face Capture	Support face image capture				
Face Attributes	Support 6 kinds of face attributes extraction: Age, Gender,Expression(Jolly/Surprise/Normal/ Rage/Sad/Disgusted/Confused/Frightened), Glasses,Mouth Mask, Moustache & Beard				
Perimeter Protection	Tripwire, Intrusion(Human & Vehicle classification)				
People Counting	Line crossing people counting, Region people counting,Loitering filter				

General Intelligence					
Event Trigger	Motion detection, Video tampering , Scene changing, Network disconnection , IP address conflict, Illegal Access,Storage anomaly				
General Intelligence	Object Abandoned/Missing				

Video					
Compression	H.265+/H.265/H.264+/H.264/H.264B/H.264H/MJPEG(sub stream)				
Streaming Capability	3 Streams				

Resolution	1080P(1920×1080)/1.3M(1280×960)/720P(1280×720)/D1(704×576/704×480)/VGA(640×480)/CIF(352×288/352×240)
Frame Rate	Main Stream: 1080P(1~25/30fps)
	Sub Stream: D1(1~25/30fps)
	Third Stream: 1080P(1~6fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 32~ 8192Kbps H.265: 19~ 7424Kbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / WDR(120dB)
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detetion	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Electronic Image Stabilization (EIS)	N/A
Smart IR	Support
Defog	Support
Digital Zoom	N/A
Flip	0°/90°/180°/270°
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)

Audio	
Compression	G.711a/G.711Mu/G.726/AAC/G.723

Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP;SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; SNMP;QoS; UPnP;NTP
Interoperability	ONVIF(Profile S/Profile G), CGI,Milestone,Genetec,P2P
Streaming Method	Unicast / Multicast
Max. User Access	20 Users
Edge Storage	NAS FTP Mirco SD card 256GB
Web Viewer	IE(versions newer than IE8), Chrome, Firefox, Safari(versions newer than Safari 12)
Management Software	Smart PSS, DSS, P2P
Smart Phone	iOS, Android

Certifications	
Certifications	CE-LVD:EN60950-1 CE-EMC:Electromagnetic Compatibility Directive 2014/30/EU FCC:47 CFR FCC Part 15, Subpart B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07

Interface

Video Interface	N/A
Audio Interface	1/1 channel In/Out
RS485	N/A
Alarm	1 channel In: 5mA 5VDC 1 channel Out: 300mA 12VDC

Electrical

Power Supply	DC12V(±30%), PoE(802.3af)(Class 0)
Power Consumption	DC12V:2.3W 4.8W(IR on) PoE:2.8W 5.5W(IR on)

Environmental

Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / 10%RH~95% RH
Storage Conditions	+5° C ~ +40° C (+41° F ~ +104° F) (daily temperature difference within 15° C/59° F) / 10%RH~95% RH
Ingress Protection	IP67
Vandal Resistance	IK10

Construction

Casing	Metal
Dimensions	Φ122mm×88.9mm (4.80"×3.50")
Net Weight	0.46Kg (1.01lb)
Gross Weight	0.62Kg (1.37lb)

Ordering Information

Type	Part Number	Description
2MP camera	DH-IPC-HFW5241RP-ASE	2MP WDR IR Dome AI Network Camera, WDR,PAL
	DH-IPC-HFW5241RN-ASE	2MP WDR IR Dome AI Network Camera, WDR,NTSC
	IPC-HFW5241RP-ASE	2MP WDR IR Dome AI Network Camera, WDR,PAL
	IPC-HFW5241RN-ASE	2MP WDR IR Dome AI Network Camera, WDR,NTSC
Accessories (optional)	PFA137	Junction box
	PFB200C	Inceiling Mount
	PFA200W	Rain Shade
	PFA123	Junction box
	PFB203W	Wall Mount
	PFA152-E	Pole Mount
	PFA106	Mount Adapter
	PFB220C	Ceiling Mount

Accessories

Optional:

PFA137
Junction boxPFB200C
Inceiling MountPFA200W
Rain ShadePFA123
Junction boxPFB203W
Wall MountPFA152-E
Pole MountPFA106
Mount AdapterPFB220C
Ceiling MountLR1002
ePoE Over Coax Converter

Junction Mount PFA137	Inceiling Mount PFB200C	Wall Mount with Rain Shade PFA200W	Junction Mount PFA123
Wall Mount PFB203W	Pole Mount PFA152-E + PFB203W	Ceiling Mount PFA106 + PFB220C	

Dimensions (mm/inch)

