
S4600-SI Series L2 Gigabits Dual Stack Intelligent Switch Datasheet

■ Product Overview

S4600-SI Series is L2 Gigabits intelligent switch designed for carrier and MAN networks. It supports comprehensive QoS, enhanced VLAN functions (VLAN VPN, Voice VLAN, QinQ, N:1 VLAN Translation etc), Ethernet Ring Protection Protocol (G.8032), classified bandwidth control, intelligent security control, OAM(Operations, Administration and Maintenance), manageability functions and Triple-Play services which fulfill the network requirements demanded by carrier network, MAN access. S4600-SI Series switch offers green features like IEEE 802.3az (Energy Efficient Ethernet), Fan-less design feature, which can dramatically lower power consumption, achieve green energy and save the cost for the carrier and MAN users.

S4600-SI Series have 6 types including **S4600-10P-SI**, **S4600-28P-SI**, **S4600-52P-SI**, **S4600-10P-P-SI***, **S4600-28P-P-SI***, **S4600-28P-PL-SI***. Equipped with the full GE ports and 4 SFP(2 SFP) uplink ports, the series integrates advanced management and security functions to provide performance and scalability.

■ Main Features

➤ Green Energy

- S4600-SI series comply with **IEEE 802.3az** (Energy-Efficient Ethernet) standard, dramatically lower power consumption
- With **Innovative port-LED Shut-off** function, the user can automatically set the switch port-LED UP or DOWN at a specified time period according to their needs to achieve functional, energy-saving correct results.
- Full account of low noise requirements of the environment, S4600-SI uses **Fanless Design and Smart fan** strategies to real-time temperature monitoring system, and reduce the noise pollution.

➤ Simple and Flexible Operation and Maintenance

- Full Ethernet **OAM** technology (IEEE802.3ah/802.1ag*), VCT, DDM (Digital Diagnostic Monitoring) and other features achieve rapid detection of the network failures; reduce operation and maintenance difficulty.

➤ Enhanced Security

- S4600-SI series provide a variety of security mechanisms like SYN Flood, Land, ICMP Flood attack prevention and other DOS class technology, BPDU Guard and Root Guard which avoid accidental topology loops and prevent illegal edge devices become root to cause unnecessary flapping.
- **IEEE 802.1X** port-based access control ensures all users are authorized before being granted access to the network. User authentication is carried out using any standard-based RADIUS server.
- Access Control Lists (**ACLs**) can be used to restrict access to sensitive network resources by denying packets and forward by different policies. User-defined ACL provides more flexible access control for users.

- S4600-SI series support **DHCP snooping**, which prevents DHCP attacks and illegal DHCP SERVER by setting trust ports and untrust ports. With DHCP Snooping binding and option82 enabled, it can combine modules like dot1x and ARP, or implement user-access-control independently.
- S4600-SI series support much more L2 security features such as **ARP guard**, **Anti-ARP scanning**, and other ARP and **MAC Security** technology to protect network security and reliability.

➤ High Reliability

- S4600-SI series support 4 Gigabit uplink ports, which could be designed to offer redundant uplinks with various ring protection applications, effectively raised the expansibility and performance of network.
- **G.8032** provides sub-50ms protection and recovery switching for Ethernet traffic in a carrier ring topology. S4600-SI series support G.8032 v2 and can be deployed in a variety of complex network topologies including single ring, tangent ring, intersecting rings, double rings and other home networking.
- Built-in **4K lightning protection** for ports on S4600-SI series effectively resists lightning, reduces equipment damage significantly.

➤ High adaptability VLAN Features

- S4600-SI series support 802.1Q and port based VLAN as well as MAC based VLAN, Voice VLAN and Protocol VLAN.
- Abundant QinQ technology including **Normal QinQ**, **Selective QinQ**, and **Flexible QinQ**, gives users maximum freedom to configure QinQ policy.
- **N:1 VLAN Translation** feature can translate multiple VLAN tags in the frames from access ports into one specified VLAN Tag. It provides a strong technical support for QoS policy convergence.

➤ Abundant Multicast Features

- S4600-SI series also support **MVR** (Multicast VLAN Register), selectively allows traffic to cross between different VLANs for bandwidth and security reasons. With MVR Trunk function, which could associate multicast VLAN to trunk port, S4600-SI series combines the VLAN data into the same link, saving lots of resources for users.
- S4600-SI series could prevent multicast traffic from flooding via IGMP Snooping, while multicast traffic is only forwarded to ports associated to multicast devices.

■ Specifications

Item	S4600-52P-SI	S4600-28P-SI	S4600-10P-SI	S4600-28P-P-SI*	S4600-28P-PL-SI*	S4600-10P-P-SI*
Ports	48 x 10/100/1000Base-T + 4 x 100/1000Base-X (SFP)	24 x 10/100/1000Base-T + 4 x 100/1000Base-X (SFP)	8 x 10/100/1000Base-T + 2 x 100/1000Base-X (SFP)	24 x 10/100/1000Base-T + 4 x 100/1000Base-X (SFP)	24 x 10/100/1000Base-T + 4 x 100/1000Base-X (SFP)	8 x 10/100/1000Base-T + 2 x 100/1000Base-X (SFP)
Performance						

Item	S4600-52P-SI	S4600-28P-SI	S4600-10P-SI	S4600-28P-P-SI*	S4600-28P-PL-SI*	S4600-10P-P-SI*
Switching Capacity	104Gbps	56Gbps	20Gbps	56Gbps	56Gbps	20Gbps
Forwarding Rate	77.4Mbps	41.7Mbps	14.88Mbps	41.7Mbps	41.7Mbps	14.88Mbps
MAC ADDRESS	16K	16K	8K	16K	16K	8K
Jumbo Frame	12K	12K	10K	12K	12K	10K
ACL Table	2048	2048	1408	2048	2048	1408
Queues per port	8	8	8	8	8	8
VLAN TABLE	4K	4K	4K	4K	4K	4K
Physical						
Dimension(WxHxD)	442mm x 220mm x 43.6mm	442mm x 220mm x 43.6mm	250mm x 180mm x 43.6mm	442mm x 220mm x 43.6mm	442mm x 220mm x 43.6mm	250mm x 180mm x 43.6mm
weight	4.70kg	2.42kg	1.1kg	TBD	TBD	TBD
Power Input	100~240VAC, 50~60Hz	100~240VAC, 50~60Hz	100~240VAC, 50~60Hz	100~240VAC, 50~60Hz	100~240VAC, 50~60Hz	100~240VAC, 50~60Hz
Power Consumption	36w	20w	20w	TBD	TBD	TBD
MTBF	>80,000 hours					
Temperature	Working 0°C~50°C, Storage -40°C~70°C					
Relative Humidity	5%~95%,non-condensing					
EMC Safety	CE, RoHS					
Physical Protection	Lightning Protection Level: 4KV					
POE	NA			IEEE 802.3af POE(15.4W) IEEE 802.3at POE+ (30W) PoE output 370w	IEEE 802.3af POE(15.4W) IEEE 802.3at POE+ (30W) PoE output 185w	IEEE 802.3af POE(15.4W) IEEE 802.3at POE+ (30W) PoE output 124w
Main Features						
Forwarding	Storage and Forwarding					
VLAN	Port-based VLAN, IEEE802.1Q, private VLAN, Protocol VLAN, Voice VLAN, MAC VLAN Normal QinQ, Selective QinQ, Flexible QinQ VLAN Translation, N:1 VLAN Translation					
DHCP	IPv4/IPv6 DHCP Client,IPv4/IPv6 DHCP Relay Option 82, Option 37/38 IPv4/IPv6 DHCP Snooping,IPv4/IPv6 DHCP Server					
Reliability	Spanning Tree	802.1D STP, 802.1W RSTP, 802.1S MSTP Root Guard, BPDU Guard, BPDU Forwarding				
	LACP	16 groups / 8 ports	8 groups / 8 ports	16 groups / 8 ports	8 groups / 8 ports	

Item	S4600-52P-SI	S4600-28P-SI	S4600-10P-SI	S4600-28P-P-SI*	S4600-28P-PL-SI*	S4600-10P-P-SI*
L2 Ring Protection	MRPP ITU-T G.8032 Loopback Detection Fast Link					
Security	IP ACL, MAC ACL, MAC-IP ACL, User-Defined ACL Time Range ACL ACL on VLAN interface Storm Control based on packets and bytes Port Security, MAC Limit based on VLAN and Port Anti-ARP-Spoofing , Anti-ARP-Scan, ARP Binding ND Snooping DAI IEEE 802.1x Authentication, Authorization, Accounting Radius, TACACS+					
Multicast	IGMP v1/v2/v3 snooping, IGMP Fast leave MVR MLD v1/v2 snooping IPv4/IPv6 DCSCM					
QoS	8 Queues Per Port Bandwidth Control Flow Redirect Classification based on ACL, VLAN ID, COS, TOS, DSCP, Policing Based on Port and VLAN Single Rate single barrel double color for Policing Remark DSCP, COS/802.1p, Precedence, TOS SP, WRR, SWRR, DWRR for Scheduling Match the IP fragmentation of message					
Maintenance and Operation Management	TFTP/FTP CLI, Telnet, Console Web/SSL (IPv4/IPv6) SSH (IPv4/IPv6) SNMPv1/v2c/v3 SNMP Trap Public & Private MIB interface RMON 1,2,3,9 Ping, Trace Route Radius Authentication Syslog (IPv4/IPv6)					

Item	S4600-52P-SI	S4600-28P-SI	S4600-10P-SI	S4600-28P-P-SI*	S4600-28P-PL-SI*	S4600-10P-P-SI*
	SNTP/NTP (IPv4/IPv6) Dual IMG, Multiple Configuration Files Port Mirror, CPU Mirror, RSPAN sFlow (S4600-28P/52P-SI) OAM EFM VCT, DDM ULDP(like Cisco UDLD) LLDP/LLDP MED					
Green Energy	IEEE 802.3az (Energy Efficient Ethernet) Fanless (10P and 28P) LED Shut-off					

■ Ordering information

Product	Description
S4600-52P-SI	L2 Gigabit Intelligent Ethernet Switch with 48 10/100/1000Base-T and 4 100/1000Base-SFP ports, 100-240VAC Power Input
S4600-28P-SI	L2 Gigabit Intelligent Ethernet Switch with 24 10/100/1000Base-T and 4 100/1000Base-SFP ports, 100-240VAC Power Input
S4600-10P-SI	L2 Gigabit Intelligent Ethernet Switch with 8 10/100/1000Base-T and 2 100/1000Base-SFP ports, 100-240VAC Power Input
S4600-10P-P-SI*	L2 Gigabit Intelligent Ethernet PoE Switch with 8*10/100/1000Base-T and 2*100/1000Base-SFP ports, 100-240VAC Power Input. 30w POE+ Supported. PoE output 124w
S4600-28P-P-SI*	L2 Gigabit Intelligent Ethernet PoE Switch with 24*10/100/1000Base-T and 4*100/1000Base-SFP ports, 100-240VAC Power Input. 30w POE+ Supported. PoE output 370w
S4600-28P-PL-SI*	L2 Gigabit Intelligent Ethernet PoE Switch with 48*10/100/1000Base-T and 4*100/1000Base-SFP ports, 100-240VAC Power Input. 30w POE+ Supported. PoE output 185w

■ Contact us

For more detail information about DCN product, please contact:

URL: <http://www.DCNglobal.com>

Email: sales@DCNglobal.com

Address: Digital Technology Plaza, NO.9 Shangdi 9th Street, Haidian District, Beijing, China