

DP-22E16C2T-VFIR3

HD720P Outdoor Vari-focal IR Bullet Camera


TURBO HD



Key features

- HD720P Video Output
- Adopt HDTVI Technology
- True Day/Night, Smart IR
- 2.8 - 12mm vari-focal lens
- Up to 40m IR distance
- IP66 weatherproof

Dimensions



DP-22E16C2T-VFIR3	
Camera	
Image Sensor	1 / 3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1280(H)*720(V)
Min. Illumination	0.01 Lux @(F1.2,AGC ON), 0 Lux with IR
Shutter speed	1/25(1/30) s to 1/50,000 s
Lens	2.8-12mm @ F1.4
	Angle of view: 80° - 27.2°
Lens Mount	φ14
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	720p@25fps/720p@30fps
HD Video Output	1 Analog HD output
S / N Ratio	More than 52dB
General	
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12V DC
Power Consumption	Max. 5W
Weather Proof Ratings	IP66
IR Range	Up to 40m
Dimensions	92 × 84.8 × 269.6mm(3.62" × 3.34" × 10.6")
Weight	1010g (2.23 lbs)