

Dynacom D780 MZ Motorized IR Dome IP Camera



- 40pcs * ¢ 5mm IR Led
- IR Range 40m
- 2.8-12mm Motorized Lens
- Built-in IR-CUT.Low power consumption
- H.264 Compression
- Support Dual-Stream
- Support ONVIF protocol
- Support RTSP browse video in real time

Model No.	D780 MZ
CAMERA	·
Max Resolution / FPS	1920x1080 / 30fps
Min. illumination	0.1Lux @ F1.2 (Color) (0 Lux IR LED On)
Video Output	Main stream:1920*1080 Deputy stream:704*576
Compression	H.264 Video Code, Support dual-stream
Bit Rate (CBR/VBR)	Support 32k-8m adjustable
Gain control	auto
Text Overlay	Time / Date / Camera / Custom OSD
Network Port	One RJ45 Ethernet interface, 10M/100M self-adaption
Standard protocol	Onvif 2.4
Network Protocols	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif
TF card	NO
3GWireless Transmission	NO
WIFI Wireless Transmission	NO
Mobile phone monitor	Support mobile phone monitor (Iphone, Windows Mobile, Android)
Operation Function	Support Web setting,OSD,real-time video transmission,support motive detection and IO alarm linkage for front end shortage/Capture/playback/download, Support Central remind and image linkage after motive detection and IO alarm linkage,support MJPEG capture,Support unit clint-side romote management software、Easy7 platform system apply
Audio interface	NO
Alarm interface	NO
Power Supply	DC9V~12V,<3W
Working Temperature	-35°C~65°C
Protection Rate	ESD 1kv



2MP





